



Safety Program Manual/ Injury & Illness Prevention Program

Digitally available at employee.sierratrim.com
Paper copy requests can be made to lamont@sierratrim.com

Revised On:
[June 27, 2026](#)

Contents

POLICY STATEMENT ON SAFETY	4
DUTIES AND RESPONSIBILITIES	5
COMPLIANCE AND ENFORCEMENT	8
Disciplinary Action:.....	8
SAFETY COMMITTEE.....	10
COMMUNICATION	11
CODE OF SAFE PRACTICES	12
BLOODBORNE PATHOGENS	26
Exposure Controls	26
Safe Work Practices.....	26
Personal Protective Equipment (PPE)	27
Post-Exposure Requirements	27
HEAT ILLNESS AND PREVENTION	29
SCAFFOLDS	31
General Requirements	31
Inspections	32
Mandatory Signs and Tags	32
Modifications	32
HAZARD IDENTIFICATION AND ASSESSMENT	33
Periodic Safety Inspections	34
Documentation of Inspections.....	34
HAZARD PREVENTION, CORRECTION, AND CONTROL	36
Techniques for Correcting Hazards	36
Documentation of Corrective Action	36
HAZARD COMMUNICATION PROGRAM	37
Introduction	37
Hazardous Material Inventory	37
Material Safety Data Sheets (MSDS)	37
Container Labeling	38
Employee Information and Training.....	38
Hazardous Non-Routine Tasks	38
Informing Outside Contractors and Vendors	38
Employee Rights Under The Hazard Communication Standard.....	39
FIRST AID AND MEDICAL EMERGENCY PROCEDURES	40
First-Aid Kits	40
First Aid	40
Accident Procedures	40
ACCIDENT / EXPOSURE INVESTIGATION	42
Responsibility for Accident Investigation	42
The Purpose of Accident Investigations:	42
What Types of Incidents Do We Investigate?	42
Procedures for Investigation of Accidents	42
Questions to Ask	43
Once the Accident Investigation is Completed	44
TRAINING AND INSTRUCTION	45
Documentation of Training	46

FIRE PREVENTION AND EMERGENCY ACTION PLAN	47
Facility Emergency Evacuation and Fire Prevention	47
During an Emergency	47
Fire Prevention in Shops and Warehouses	48
FLEET AND DRIVER SAFETY.....	49
Driver Selection	49
Driver Training.....	49
Company Vehicle Use Policy	49
Vehicle Inspection & Preventive Maintenance	50
Accident Investigation.....	50
Auto Accident Preventability Guide	50
FALL PROTECTION	55
Fall Protection is Required	55
Fall Protection Types	55
Standard Guardrails, Safety Cables, or Covers.....	55
Personal Fall Arrest Systems	56
Positioning Device Systems.....	57
Personal Fall Restraint.....	58
RESPIRATORY PROTECTION.....	59
General Respiratory Protection Guidelines:.....	59
Respirator Selection Requirements.....	60
Medical Evaluation Procedures.....	61
Fit Testing	62
Usage Rules	63
Maintenance, Inspection and Care of Respirators.....	64
Training	65
Program Evaluation.....	65
Recordkeeping.....	66
Procedures for Cleaning Respirators.....	66
Mandatory Information for Employees Using Respirators When Not Required	67
ELECTRICAL & LOCK-OUT / TAG-OUT PROGRAM	69
All Equipment and Installations	69
Energized Equipment or Systems.....	69
De-energized Equipment or Systems	70
Energizing (or Re-energizing) Equipment or Systems	70
Accident Prevention Tags.....	71
Lock-out / Tag-out.....	71
Sequence of Lockout Procedure	71
Procedure Involving More Than One Person	72
Testing Equipment during Lockout	72
Restoring Equipment to Service.....	72
CONFINED SPACE OPERATIONS	73
Definitions	73
Typical Confined Spaces:.....	73
Prior to Confined Space Entry:.....	74
Confined Space Entry if Tests Show No Hazard	74
Confined Space Entry if Tests Show Hazards are Present or are Likely to Develop	74
Confined Spaces Where Dangerous Air Contamination Cannot be Removed by Ventilation	75
FORKLIFTS.....	76
General.....	76
Training Program Implementation.....	76

Sierra Trim, Inc.

IIPP/SAFETY MANUAL

Training Program Content.....	76
Refresher Training and Evaluation.	77
Avoidance of Duplicative Training.....	77
Certification.....	78
RECORDKEEPING	79
APPENDIXES	80
HAZARD ASSESSMENT AND CORRECTION RECORD	81
ACCIDENT / EXPOSURE INVESTIGATION REPORT.....	83
WORKER TRAINING AND INSTRUCTION RECORD	84
EMPLOYEE SAFETY CONTACT REPORT	85
NEW EMPLOYEE SAFETY ORIENTATION	86
CODE OF SAFE PRACTICES RECEIPT	87
SAFETY COMMITTEE MEETING MINUTES	88
Date of Committee Meeting	88
Minutes prepared by.....	88
SAFETY MEETING MINUTES.....	90
Company	90
Presenter.....	90
FACILITY INSPECTION CHECKLIST	91
GENERAL WORK ENVIRONMENT	92

POLICY STATEMENT ON SAFETY

The management of this company is very interested in working with you to provide a safe place in which to work. The prevention of accidents and injuries to our employees is the prime objective.

All company personnel are expected to take an active and constant interest in the prevention of accidents. We call upon all employees to use good common sense and in all their actions, take a second to think of the consequences to your fellow employees. We cannot overemphasize that all employees must do their part to minimize accidents.

Please show your support by demonstrating the following:

1. OBSERVING COMPANY SAFETY RULES.
2. KEEPING WORK AREAS FREE OF UNSAFE CONDITIONS.
3. AVOIDING AND ELIMINATING UNSAFE ACTS.
4. PROMPTLY REPORTING UNSAFE ACTS AND CONDITIONS.
5. REPORTING ALL ACCIDENTS IMMEDIATELY.

Accidents cause suffering and pain. We value each of you as individuals and hope you will cooperate with us in this important endeavor.

Any constructive criticism or suggestions toward improving safety on any of our jobs will be given prompt and careful consideration.

Sincerely,

William Snow
Sierra Trim Inc.
(916) 259-2966

DUTIES AND RESPONSIBILITIES

A successful Safety and Injury and Illness Prevention Program can only be achieved and maintained when there is active interest, participation, and accountability at all a level of the organization. To ensure this, the company, delegates the following safety duties to all management personnel. In some cases employees will need to perform safety duties outside their regular responsibilities to prevent accidents.

The Safety Program Administrator must plan, organize, and administer the program by establishing policy, setting goals and objectives, assigning responsibility, motivating subordinates, and monitoring results. Company management will support and maintain an ongoing Safety and Injury and Illness Prevention Program through the following:

1. Providing clear understanding and direction to all management and employees regarding the importance of safety through the development, implementation, monitoring and revision of policy and procedures.
2. Providing financial support for the Safety / Injury and Illness Prevention Program through the provision of adequate funds for the purchase of necessary safety materials, safety equipment, proper personal protective equipment, adequate time for employee safety training, and maintenance of tools and equipment.
3. Overseeing development, implementation, and maintenance of the safety manual, IIPP, and other required safety programs.
4. Maintaining a company commitment to accident prevention by expecting safe conduct on the part of all managers, supervisors, and employees.
5. Holding all levels of management and employees accountable for accident prevention and safety.
6. Reviewing all accident investigations to determine corrective action.

Managers and Supervisors play a key role in the prevention of accidents on the job. They have direct contact with the employees and know the safety requirements for various jobs. Safety responsibilities for these individuals include:

1. Enforce all safety rules in the Code of Safe Practices and ensure safe work procedures.
2. Verifying corrective action has been taken regarding safety hazards and accident investigations.
3. Conducting periodic documented inspections of the work sites to identify and correct unsafe actions and conditions that could cause accidents.
4. Act as a leader in company safety policy and setting a good example by following all safety rules.
5. Becoming familiar with local, state, and federal safety regulations. The Safety Coordinator is available for assistance.
6. Train all new and existing employees in proper safety procedures and the hazards of the job.
7. Instruct all employees, under their supervision, in safe work practices and job safety requirements.
8. Hold weekly safety meetings with employees.
9. Ensure employee proficiency when assigning work requiring specific knowledge, special operations or equipment.

10. Ascertain that all machinery, equipment, and workstations are maintained in safe working condition and operate properly.
11. Correct unsafe acts and conditions that could cause accidents.
12. Communicate with all employees about safety and accident prevention activities.
13. Correct the cause of any accident as soon as possible.
14. Ascertain that proper first aid and fire fighting equipment is maintained and used when conditions warrant its use.
15. Maintain good housekeeping conditions at all times.
16. Investigate all injuries and accidents to determine their cause and potential corrective action.
17. Ascertain that all injuries involving our employees that require medical attention are properly treated and promptly reported to the office.

The Safety Program Administrator acts as a safety resource for the company and is responsible for maintaining program records. They will also be our primary person to deal with outside agencies regarding the safety program and its contents. Additional duties include:

1. Coordination of all loss prevention activities as a representative of management. Acting as a consultant to management in the implementation and administration of the Safety Program.
2. Develop and implement loss prevention policies and procedures designed to ensure compliance with the applicable rules and regulations of all federal, state, and local agencies.
3. Review all accident reports to determine cause and preventability.
4. Conduct periodic reviews of the program and job sites to evaluate performance, discuss problems and help solve them.
5. Consult with representatives of our insurance companies in order that their loss control services will support the Safety Program.
6. Review Workers' Compensation Claims. Help supply the insurance carrier with information about injured employees in order to keep loss reserves as low as possible.

Every employee is responsible for working safely, both for self-protection and for protection of fellow workers. Employees must also support all company safety efforts. Specific employee safety responsibilities include:

1. If you are unsure how to do any task safely, ask your supervisor.
2. Read and abide by all requirements of the Safety Manual.
3. Know and follow the Code of Safe Practices and all company safety policies and rules.
4. Wear all required personal protective equipment.

5. Report all accidents and injuries, no matter how minor, to your supervisor immediately.
6. Do not operate any equipment you have not been trained and authorized to use.
7. Report any safety hazards or defective equipment immediately to your supervisor.
8. Do not remove, tamper with or defeat any guard, safety device or interlock.
9. Never use any equipment with inoperative or missing guards, safety devices or interlocks.
10. Never possess, or be under the influence of, alcohol or controlled substances while on the premises.
11. Never engage in horseplay or fighting.
12. Participate in, and actively support, the company safety program.

COMPLIANCE AND ENFORCEMENT

The compliance of all employees with our Safety Manual / IIPP is mandatory and shall be considered a condition of employment.

The following programs will be utilized to ensure employee compliance with the safety program and all safety rules.

- Training programs
- Retraining
- Disciplinary action
- Optional safety incentive programs

Training Programs

The importance of safe work practices and the consequences of failing to abide by safety rules will be covered in the New Employee Safety Orientation and safety meetings. This will help ensure that all employees understand and abide by company safety policies.

Retraining

Employees that are observed performing unsafe acts or not following proper procedures or rules will be retrained by their supervisor. A Safety Contact Report may be completed by the supervisor to document the training. If multiple employees are involved, additional safety meetings will be held.

Safety Incentive Programs

Although strict adherence to safety policies and procedures is required of all employees, the company may choose to periodically provide recognition of safety-conscious employees and job sites without accidents through a safety incentive program.

Disciplinary Action:

The failure of an employee to adhere to safety policies and procedures can have a serious impact on everyone concerned. An unsafe act can threaten not only the health and well-being of the employee committing the unsafe act but can also affect the safety of his/her coworkers and customers. Accordingly, any employee who violates any of the company's safety policies will be subject to disciplinary action.

Note: Failure to promptly report any on-the-job accident or injury, on the same day as occurrence, is considered a serious violation of the Company's Code of Safe Practices. Any employee who fails to immediately report a work-related accident or injury, no matter how minor shall be subject to disciplinary action.

Employees will be disciplined for infractions of safety rules and unsafe work practices that are observed, not just those that result in an injury. Often, when an injury occurs, the accident investigation will reveal that the injury was caused because the employee violated an established safety rule and/or safe work practice(s). In any disciplinary action, the supervisor should be cautious that discipline is given to the employee for safety violations, and not simply because the employee was injured on the job or filed a Workers' Compensation claim.

Violations of safety rules and the Code of Safe Practices are to be considered equal to violations of other company policy. Discipline for safety violations will be administered in a manner that is consistent with the company's system of progressive

discipline. If, after training, violations occur, disciplinary action will be taken as follows:

1. Oral warning. Document it, including date and facts on the "Safety Contact Report" form. Add any pertinent witness statements. Restate the policy and correct practice(s).
2. Written warning. Retrain as to correct procedure/practice.
3. Written warning with suspension.
4. Termination

As in all disciplinary actions, each situation is to be carefully evaluated and investigated. The step taken in the disciplinary process will depend on the severity of the violation, employee history, and regard to safety. Managers and supervisors should consult with the office if there is any question about whether disciplinary action is justified. Employees may be terminated immediately for willful or extremely serious violations. Union or contract employees are entitled to the grievance process specified by their contract.

Note: You must be consistent in the enforcement of all safety rules.

Purpose

The purpose of the safety committee is to promote workplace safety and health by increasing the communication, education, and involvement of company personnel. The Safety Program Administrator holds permanent membership in the safety committee in order to ensure that responsibility is delegated appropriately.

Membership

The safety program administrator shall represent the safety committee membership, supervisory and non-supervisory employees, with non-supervisory employees being the majority. The employees on the committee will be volunteers and will serve on the committee for a two-year term (except for the safety program administrator).

Meetings

There will be one committee meeting every quarter. The dates will be determined by the members' schedules. All committee meetings and training will be conducted during working hours. All committee members will be compensated at their normal rate of pay during the meetings, committee specific training, and any other committee related duties.

Emergency Meetings

The committee may conduct an emergency meeting if the majority of the members feel that such a meeting is necessary. If an emergency meeting is called outside regular working hours, the non-salaried employees will be compensated at their overtime rate.

Recordkeeping

Complete and accurate records of the functions and proceedings of the safety committee will be maintained by the Corporate Office with copies distributed to each worksite.

Meetings will be recorded, and minutes will be prepared following each committee meeting. Copies of the minutes will be kept at each worksite. Any employee will make these documents available for inspection upon request.

Communication

All original written communications between the company and the committee, or true copies thereof, will be maintained at each jobsite and made readily available for inspection by government agencies.

The company shall issue a timely written response to all written questions and recommendations from the safety committee.

This section establishes procedures designed to develop and maintain employee involvement and interest in the Safety Manual. These activities will also ensure effective communication between management and employees on safety related issues that is of prime importance to the company. The following are some of the safety communication methods that may be used:

1. Periodic safety meetings with employees that encourage participation and open, two-way communication.
2. New employee safety orientation and provision of the Code of Safe Practices.
3. Provision and maintenance of employee bulletin boards discussing safety issues, accidents, and general safety suggestions.
4. Written communications from management or the Safety Program Manager, including memos, postings, payroll stuffers, and newsletters.
5. Anonymous safety suggestion program.

Employees will be kept advised of highlights and changes relating to the safety program. Management shall relay changes and improvements regarding the safety program to employees, as appropriate. Employees will be involved in future developments and safety activities, by requesting their opinions and comments, as necessary.

All employee-initiated safety related suggestions shall be properly answered, either verbally or in writing, by the appropriate level of management. Unresolved issues shall be relayed to the program manager or safety committee members.

All employees are encouraged to bring any safety concerns they may have to the attention of management. The company will not discriminate against any employee for raising safety issues or concerns.

The company also has a system of anonymous notification whereby employees who wish to inform the company of workplace hazards without identifying themselves may do so by phoning or sending written notification to the main office.

ALL EMPLOYEES

Housekeeping

1. Do not place material such as boxes or trash in walkways and passageways.
2. Do not block or obstruct stairwells, exits or accesses to safety and emergency equipment such as fire extinguishers or fire alarms.
3. Do not store or leave items on stairways.
4. Straighten or remove rugs and mats that do not lie flat on the floor.
5. Keep floors clear of items such as paper clips, pencils, tacks or staples.
6. Clean up spills immediately by using a paper towel, rag, or mop and bucket.
7. Clean up any broken glass using a dustpan and broom. Do not pick up broken glass with your bare hands.
8. Use caution signs/cones to barricade slippery areas such as freshly mopped floors.
9. Mop up standing water upon discovery.

Lifting Procedures

General

1. Test the weight of the load before lifting by pushing the load along its resting surface.
2. If the load is too heavy or bulky, use lifting and carrying aids such as hand trucks, dollies, pallet jacks and carts, or get assistance from a co-worker.
3. Never lift anything if your hands are greasy or wet.
4. Wear protective gloves when lifting objects with sharp corners or jagged edges.

When lifting

1. Face the load.
2. Position your feet 6"-12" apart with one foot slightly in front of the other.
3. Bend at the knees, not at the back.
4. Keep your back straight.
5. Get a firm grip on the object with your hands and fingers. Use handles when present.
6. Hold objects as close to your body as possible.
7. Perform lifting movements smoothly and gradually; do not jerk the load.
8. If you must change direction while lifting or carrying the load, pivot your feet and turn your entire body. Do not twist at the waist.
9. Set down objects in the same manner as you picked them up, except in reverse.
10. Do not lift an object from the floor to a level above your waist in one motion. Set the load down on a table or bench and then adjust your grip before lifting it higher.

Ladders and Step Ladders

General

1. Do not use ladders that have loose rungs, cracked or split side rails, missing rubber foot pads, or are otherwise visibly damaged.
2. Keep ladder rungs clean of grease. Remove buildup of material such as dirt or mud.
3. When performing work from a ladder, face the ladder and do not lean backward or sideways from the ladder.
4. Do not stand on the top two rungs of any ladder.
5. Do not stand on a ladder that wobbles, or that leans to the left or right.
6. Do not try to "walk" a ladder by rocking it. Climb down the ladder, and then move it.

Climbing a Ladder

1. Face the ladder when climbing up or down.
2. Allow only one person on the ladder at a time.
3. Do not carry items in your hands while climbing up or down a ladder.

4. Maintain a three-point contact by keeping both hands and one foot or both feet and one hand on the ladder at all times when climbing up or down.

Hazardous Materials

1. Follow the instructions on the label and in the corresponding Material Safety Data Sheet (MSDS) for each chemical product used in your workplace.
2. Do not use chemicals from unlabeled containers.

Personal Protective Equipment

1. Wear earplugs or earmuffs in areas posted "Hearing Protection Required."
2. Wear safety glasses or face shields in areas posted "Eyewear Protection Required."
3. Wear hard hats or approved head protection in areas posted "Hard Hat Protection Required."

OFFICE PERSONNEL

Office Safety

General

1. Clean up spills or leaks immediately by using a paper towel, rag or a mop and bucket.
2. Do not kick objects out of your pathway; pick them up or push them out of the way.
3. Do not throw matches, cigarettes or other smoking materials into trash baskets.
4. Keep floors clear of items such as paper clips, pencils, tacks or staples.
5. Do not block your view by carrying large or bulky items; use a dolly or hand truck or get assistance from a fellow employee.
6. Store sharp objects, such as pens, pencils, and letter openers or scissors in drawers or with the points down in a container.
7. Carry pencils, scissors and other sharp objects with the points down.
8. Use a ladder or step stool to retrieve or store items that are located above your head.
9. Do not store or leave items on stairways or walkways.
10. Do not run on stairs or take more than one step at a time.
11. Do not jump from ramps, platforms, ladders or step stools.
12. Keep doors in hallways fully open or fully closed.
13. Use handrails when ascending or descending stairs or ramps.
14. Obey all posted safety and danger signs.

Furniture Use

1. Open one file cabinet drawer at a time.
2. Close drawers and doors immediately after use.
3. Use the handle when closing doors, drawers and files.
4. Put heavy files in the bottom drawers of file cabinets.
5. Do not tilt the chair you are sitting in on its back two legs.
6. Do not stand on furniture to reach high places.

Equipment Use

1. Keep the paper cutter handle in the closed/locked position when it is not in use.
2. Do not use paper-cutting devices if the finger guard is missing.
3. Use a staple remover, not your fingers, for removing staples.
4. Do not use extension or power cords that have the ground prong removed or broken off.
5. Do not use frayed, cut or cracked electrical cords.
6. Use a cord cover or tape the cord down when running electrical or other cords across aisles, between desks or across entrances/exits.
7. Do not connect multiple electrical devices into a single outlet.
8. Turn off and unplug office machines before adjusting, lubricating or cleaning them.

9. Do not use fans that have excessive vibration, frayed cords or missing guards.
10. Do not place floor type fans in walkways, aisles or doorways.

FORK LIFT AND HOIST OPERATORS

General Machine Shop Safety

1. Read and obey safety warnings posted on or near any machinery.
2. Long hair must be contained under a hat or hair net, regardless of gender.

General Hand Tool Safety

1. Use tied off containers to keep tools from falling off of cranes and other elevated work areas.
2. Do not use a tool if its handle has splinters, burrs, cracks, splits or if the head of the tool is loose.
3. Do not use impact tools, such as hammers, that have mushroomed heads.
4. When handing a tool to another person, direct sharp points and cutting edges away from yourself and the other person.
5. When using knives, shears or other cutting tools, cut in a direction away from your body.
6. Do not carry sharp or pointed hand tools, such as screwdrivers, in your pocket unless the tool or pocket is sheathed.
7. Do not perform "make-shift" repairs to tools.
8. Do not use "cheaters" on load binders or "boomers."
9. Do not carry tools in your hand when climbing. Carry tools in tool belts or hoist the tools to the work area with a hand line.
10. Do not throw tools from one location to another, from one employee to another, from scaffolds or other elevated platforms.

Forklifts

Pre-Use Inspection – Do not use forklift if any of the following conditions exist:

1. The mast has broken or cracked weld-points.
2. The roller tracks are not greased, or the chains are not free to travel.
3. Forks are unequally spaced, or cracks exist along the blade or at the heels.
4. Hydraulic fluid levels are low.
5. Hydraulic line and fitting have excessive wear or are crimped.
6. Fluid is leaking from the lift or the tilt cylinders.
7. The hardware on the cylinders is loose.
8. Tires are excessively worn, split or have missing tire material.
9. Air filled tires are not filled to the operating pressure indicated on the tire.
10. Batteries have cracks or holes, uncapped cells, frayed cables, broken cable insulation, loose connections or clogged vent caps.

Starting the Forklift

- Apply the foot brake and shift gears to neutral before turning the key.

Picking Up a Load

1. Square up on the center of the load and approach it straight on with the forks in the travel position.
2. Stop when the tips of your forks are about a foot from the load.
3. Level the forks and slowly drive forward until the load is resting against the backrest of the mast.
4. Lift the load high enough to clear whatever is under it.
5. Back up about one foot, and then slowly and evenly tilt the mast backwards to stabilize the load.

Putting a Load Down

1. Square up and stop about one foot from desired location.
2. Level the forks and drive to the loading spot.
3. Slowly lower the load to the floor.
4. Tilt the forks slightly forward so that you do not hook the load.

5. When the path behind you is clear of obstructions, back straight out until the forks have cleared the pallet.

Stacking One Load on Top of Another

1. Stop about one foot away from the loading area and lift the mast high enough to clear the top of the stack.
2. Slowly move forward until the load is squarely over the top of the stack.
3. Level the forks and lower the mast until the load is no longer supported by the forks.
4. Look over both shoulders for obstructions and back straight out if the path is clear.

Forklift Safety Rules

1. Do not exceed the lift capacity of the forklift. Read the lift capacity plate on the forklift if you are unsure.
2. Follow the manufacturer's guidelines concerning changes in the lift capacity before adding an attachment to a forklift.
3. Lift the load an inch or two to test for stability: If the rear wheels are not in firm contact with the floor, take a lighter load or use a forklift with a higher lift capacity.
4. Do not raise or lower a load while you are en route. Wait until you are in the loading area and have stopped before raising or lowering the load.
5. After picking up a load, adjust the forks so that the load is tilted slightly backward for added stability.
6. Drive with the load at a ground clearance height of 4-6 inches at the tips and 2 inches at the heels in order to clear most uneven surfaces and debris.
7. Drive at a walking pace and apply brakes slowly to stop when driving on slippery surfaces such as wet floors.
8. Do not drive over objects in your pathway.
9. Do not drive into an area with a ceiling height that is lower than the height of the mast or overhead guard.
10. Steer wide when making turns.
11. Do not drive up to anyone standing or working in front of a fixed object such as a wall.
12. Do not drive along the edge of an unguarded elevated surface such as a loading dock or staging platform.
13. Obey all traffic rules and signs.
14. Sound horn when approaching blind corners, doorways or aisles to alert other operators and pedestrians.
15. Stay a minimum distance of three truck lengths from other operating mobile equipment.
16. Drive in reverse and use a signal person when your vision is blocked by the load.
17. Look in the direction that you are driving; proceed when you have a clear path.
18. Do not use bare forks as a man-lift platform.
19. Do not drive the forklift while people are on the attached man-lift platform.
20. Drive loaded forklifts forward up ramps.
21. Raise the forks an additional two inches to avoid hitting or scraping the ramp surface as you approach the ramp.
22. Drive loaded forklifts in reverse when driving down a ramp.
23. Drive unloaded forklifts in reverse when going up a ramp and forward when going down a ramp.
24. Do not attempt to turn around on a ramp.
25. Do not use "Reverse" to brake.
26. Lower the mast completely, turn off the engine and set the parking brake before leaving your forklift.

Loading Docks

1. Keep the forklift clear of the dock edge while vehicles are backing up to the dock.
2. Do not begin loading or unloading until the supply truck has come to a complete stop, the engine has been turned off, the dock lock has been engaged and the wheels have been chocked.
3. Attach the bridge or dock plate before driving the forklift into the truck.
4. Do not drive the forklift into a truck bed that has soft or loose decking or other unstable flooring.
5. Drive straight across the bridge plates when entering or exiting the trailer.
6. Use dock lights or headlights when working in a dark trailer.

Cranes and Hoists

1. Do not use load hooks or chains that are cracked, bent, elongated or broken.
2. Do not use cranes that do not have their rated load capacity indicated on each side of the crane or on its load block.

3. Passengers are not permitted to ride inside the operator's cab of a truck crane.
4. Keep crane windows clean. Do not use a crane if its windows are broken.
5. Do not exceed posted weight limits on hoists.
6. Do not operate a crane on soft ground without cribbing and mats.
7. Fully extend outriggers before attempting a lift.
8. Stay outside the barricades of the posted swing radius.
9. Do not perform any crane retrofits or modifications without the manufacturer's approval.
10. Do not leave the crane unattended with a hoisted load.
11. Do not hoist loads over people.
12. Do not drive on the road shoulders.
13. Wear high visibility vests.
14. Wear the prescribed personal protective equipment such as hard hat, goggles, gloves, dust masks and hearing protection when operating a hoist.

Signalman

1. Wear high visibility vests while working as a signalman.
2. Only follow the signals of the person designated to give you signals when operating a crane.
3. Replace the belts, gears or rotating shaft guards after servicing a crane; do not use the crane if guards are missing from these areas.
4. Wear the prescribed personal protective equipment such as hard hat, goggles, gloves, dust masks and hearing protection when operating a hoist.

PRODUCTION/ASSEMBLY PERSONNEL

Housekeeping

1. Do not use gasoline for cleaning purposes.
2. Do not throw matches, cigarettes or other smoking materials into trash baskets.
3. Keep floors clear of items such as metal chips, bolts, oily rags, metal shavings or metal dust.
4. Store rags that have oil or cutting fluids on them in closed metal containers labeled "oily rags."
5. Close the lids of containers of cutting fluids and solvents tightly after each use or when not being used.
6. Use brushes or vacuum machinery to remove metal chips, shavings and other debris from the drill table. Do not use your bare hands.
7. Sweep up shavings from around equipment such as drill presses, lathes or planers by using a broom and a dustpan.

Machine Safety

1. Replace the guards before starting machines, after making adjustments or repairs.
2. Do not remove, alter or bypass any safety guards or devices when operating mechanical equipment such as mechanical power presses, press brakes, metal working lathes, cutting, notching, or bending and forming machinery.
3. Do not wear loose clothing or jewelry in the machine shop.
4. Long hair must be contained under a hat or hair net, regardless of gender.
5. Read and obey safety warnings posted on or near any machinery.
6. Do not try to stop a work piece as it goes through any machine. If the machine becomes jammed, disconnect the power before clearing the jam.

Grinders

1. Do not use grinding wheels that have chips, cracks or grooves.
2. Do not use the grinding wheel if it wobbles. Tag it "Out of Service".
3. Adjust the tongue guard so that it is no more than 1/4 inch from the grinding wheel.
4. Do not try to stop the wheel with your hand, even if you are wearing gloves.

Drills

- Do not use dull, cracked or bent drill bits.

Hydraulic/Pneumatic Tools

1. Do not point a compressed air hose at bystanders or use it to clean your clothing.
2. Tag defective or damaged tools "Out of Service" to prevent usage of the tool.
3. Do not use tools that have handles with burrs or cracks.
4. Do not use compressors if their belt guards are missing. Replace belt guards before use.
5. Turn the tool "off" and let it come to a complete stop before leaving it unattended.
6. Disconnect the tool from the airline before making any adjustments or repairs to the tool.

General Hand Tool Safety

1. Tag worn, damaged or defective tools "Out of Service" and do not use them.
2. Do not use a tool if its handle has splinters, burrs, cracks, splits or if the head of the tool is loose.
3. Do not use impact tools such as hammers, chisels, punches or steel stakes that have mushroomed heads.
4. When handing a tool to another person, direct sharp points and cutting edges away from yourself and the other person.
5. When using knives, shears or other cutting tools, cut in a direction away from your body.
6. Do not carry sharp or pointed hand tools such as screwdrivers, scribes, snips, scrapers, chisels or files in your pocket unless the tool or pocket is sheathed.
7. Do not perform "make-shift" repairs to tools.
8. Do not throw tools from one location to another or from one employee to another.
9. Transport hand tools only in toolboxes or tool belts. Do not carry tools in your clothing.

Powder Actuated Tools

1. Wear impact resistant safety goggles or face shields when operating any powder actuated tools.
2. When using powder-actuated tools, do not drive fasteners into structural steel without first looking to see if the steel is backed by a steel plate or barricade, and to see if all personnel are away from the direct line of fire.
3. Do not attempt to fasten through a pre-drilled hole unless the powder-actuated tool has a hole locator.
4. Keep your head and body behind the powder-actuated tool when firing it.
5. Do not fasten steel beams at a distance closer than 1/2 inch from the edge of the steel.
6. Before using powder actuated tools do not alter, bypass, or remove the shield or guard at the muzzle end of the powder-actuated tool.
7. Do not load a powder-actuated tool until you are ready to fire it.

Riveting and Bolting

1. Do not use your hands to guide a bit into place when riveting or bolting steel.
2. Disconnect the snap and plunger from an air hammer when it is not in use.
3. Do not pass air-powered tools by the hose from one worker to another.
4. Do not throw material from one person to another. Use tag lines and a basket to hoist bolts, washers, drift pins and tools.
5. Use a receptacle or a net to catch rivets or bolts that are knocked off or backed out from your work area.
6. Do not carry nuts, bolts, rivets or drift pins in your hands or pockets; use the carrying/storing container provided for this purpose.

Lifting Equipment (Chains, Cables, Ropes, Slings)

1. Do not use chain slings if links are cracked, twisted, stretched or bent.
2. Fabricate all wire in wire rope slings by using thimbles; do not form eyes by using wire clips or knots.
3. Do not shorten slings by using make-shift devices such as knots or bolts.
4. Do not use a kinked chain.
5. Protect slings from the sharp edges of their loads by placing pads over the sharp edges of the items that have been loaded.
6. Do not place your hands between the sling and its load when the sling is being tightened around the load.
7. Wear work gloves when handling rough, sharp-edged or abrasive material such as chains, cables ropes or slings.

8. Do not alter or remove the safety latch on hooks. Do not use a hook that does not have a safety latch, or if the safety latch is bent.
9. Lift the load from the center of hooks, not from the point.

Personal Protective Equipment

1. Wear safety glasses such as burning goggles or grinding goggles or face shields when operating grinders, forges, lathes, planers or sanders.
2. Wear face shields over goggles or safety glasses during open furnace, hot dipping, metal plating or gas cutting operations.
3. Wear chemical goggles when using, applying or handling chemical liquids or powders from containers labeled "CAUSTIC" or "CORROSIVE."
4. Do not continue to work if your safety glasses become fogged. Stop work and clean the glasses until the lenses are clear and defogged.
5. When welding, wear a welding helmet with filter plates and lenses, welding gloves, a long sleeve shirt, long pants, and an apron.
6. Insulated work gloves are required for all welders when using welding equipment.
7. Wear ear plugs or earmuffs in areas posted "Hearing Protection Required."
8. Do not wear contact lenses when welding.

Hazardous Materials

1. Do not store chemical containers labeled "Oxidizer" with containers labeled "Corrosive" or "Caustic."
2. Use personal protective clothing or equipment such as neoprene gloves, rubber boots, shoe covers, rubber aprons, and protective eyewear, when using chemicals labeled "Flammable", "Corrosive", "Caustic" or "Poisonous."
3. Do not use protective clothing or equipment that has split seams, pin holes, cuts, tears, or other signs of visible damage.
4. Each time you use your gloves, wash your gloves before removing them using cold tap water and normal hand washing motion. Always wash your hands after removing the gloves.

Hand Tools

1. Use tied-off containers to keep tools from falling off scaffolds and other elevated work platforms.
2. Keep the blades of all cutting tools sharp.
3. Carry all sharp tools in sheaths or holsters.
4. Tag worn, damaged, or defective tools "Out of Service" and do not use them.
5. Do not use a tool if its handle has splinters, burrs, cracks, splits or if the head of the tool is loose.
6. Do not use impact tools such as hammers, chisels, punches, or steel stakes that have mushroomed heads.
7. When handing a tool to another person, direct sharp points and cutting edges away from yourself and the other person.
8. Do not chop at heights above your head when working with a hand axe.
9. Do not carry sharp or pointed hand tools such as screwdrivers, scribes, aviation snips, scrapers, chisels or files in your pocket unless the tool or pocket is sheathed.
10. Do not perform "make-shift" repairs to tools.
11. Do not use "cheaters" on load binders or "boomers."
12. Do not carry tools in your hand when climbing. Carry tools in tool belts or hoist the tools to the work area with a hand line.
13. Do not throw tools from one location to another, from one employee to another, from scaffolds or other elevated platforms.

Chisels

1. Keep the cutting edge of the chisel sharp.
2. Do not use chisels with damaged striking ferrules.
3. Hold a chisel with a tool holder if possible.
4. Clamp a small work piece in a vise and chip towards the stationary jaw when working with a chisel.

Clamps

1. Do not use the C-clamp for hoisting materials.
2. Do not use the C-clamp as a permanent fastening device.

Files/Rasps

1. Do not use a file as a pry bar, hammer, screwdriver, or chisel.
2. When using a file or a rasp, grasp the handle in one hand and the toe of the file in the other.
3. Do not hammer on a file.

Hammers

1. Use a claw hammer for pulling nails and driving nails.
2. Do not strike nails or other objects with the cheek of the hammer.
3. Do not strike a hardened steel surface, such as a cold chisel, with a claw hammer.
4. Do not strike one hammer against another hammer.
5. Do not use a hammer if your hands are oily, greasy, or wet.
6. Do not use a hammer as a wedge, a pry bar or for pulling large spikes.
7. Use only a sledge-type hammer on a striking face wrench.

Knives/Sharp instruments

1. When handling knife blades and other cutting tools, direct sharp points and edges away from you.
2. Store knives in knife blocks or in sheaths after use.
3. Do not use knives with dull blades.
4. Do not use honing steels that do not have disc guards.
5. Do not attempt to catch a falling knife.
6. Use knives for the operation for which they are named.
7. Do not use knives with broken or loose handles.
8. Do not use knives as screwdrivers, pry bars, can openers or ice picks.
9. Do not pick up knives by their blades.
10. Carry knives with their tips pointed towards the floor.

Pliers

1. Do not attempt to force pliers by using a hammer on them.
2. Do not slip a pipe over the handles of pliers to increase leverage.
3. Use pliers with insulated handles for electrical work.
4. Do not use pliers that are cracked, broken, or sprung.
5. When using diagonal cutting pliers, shield the loose pieces of cut material from flying into the air by using a cloth or your gloved hand.

Saws

1. Do not use an adjustable blade saw such as a hacksaw, coping saw, keyhole saw, or bow saw, if the blade is not taut.
2. Do not use a saw that has dull saw blades.
3. Keep hands and fingers away from the saw blade while using the saw.
4. Do not carry a saw by the blade.
5. When using a handsaw, hold the work piece firmly against the worktable.
6. Do not use woodworking equipment such as circular saws, radial saws, or jointers if they do not have guards on the saw blade.
7. Keep control of saws by decreasing downward pressure at the end of the stroke.
8. When operating scroll saws, stop the machine before removing scrap pieces from the table.
9. Clamp work when using a hole saw.

Screwdrivers

1. Always match the size and type of screwdriver blade to fit the head of the screw.

2. Do not hold the work piece against your body while using a screwdriver.
3. Do not put your fingers near the blade of the screwdriver when tightening a screw.
4. Use an awl, drill or a nail to make a starting hole for screws.
5. Do not force a screwdriver by using a hammer or pliers on it.
6. Do not use a screwdriver as a punch, chisel, pry bar or nail puller.
7. Use a screwdriver that has an insulated handle for electrical work.
8. Do not use a screwdriver if your hands are wet, oily, or greasy.
9. Do not use a screwdriver to test the charge of a battery.
10. When using a spiral ratchet screwdriver, push down firmly and slowly.

Snips

1. Wear safety glasses or safety goggles when using snips to cut materials.
2. Wear work gloves when cutting materials with snips.
3. Do not use straight cut snips to cut curves.
4. Keep the blade aligned by tightening the nut and bolt on the snips.
5. Do not use snips as a hammer, screwdriver, or pry bar.
6. Use the locking clip on the snips after use.

Vises

1. When clamping a long work piece in a vise, support the far end of the work piece by using an adjustable pipe stand, sawhorse, or box.
2. Position the work piece in the vise so that the entire face of the jaw supports the work piece.
3. Do not use a vise that has worn or broken jaw inserts or has cracks or fractures in the body of the vise.
4. Do not slip a pipe over the handle of a vise to gain extra leverage.

LADDERS AND STEP LADDERS

1. Read and follow the manufacturer's instructions label affixed to the ladder if you are unsure how to use the ladder.
2. Do not use ladders that have loose rungs, cracked or split side rails, missing rubber footpads, or are otherwise visibly damaged.
3. Keep ladder rungs clean and free of grease. Remove material buildup such as dirt or mud.
4. Do not use a metal ladder on rooftops or within 50 feet of electrical power lines.
5. Allow only one person on the ladder at a time.
6. Face the ladder when climbing up or down.
7. Maintain a three-point contact by keeping both hands and one foot or both feet and one hand on the ladder at all times when climbing up or down.
8. When performing work from a ladder, face the ladder and do not lean backward or sideways from the ladder.
9. Do not stand on the top two rungs of any ladder.
10. Do not stand on a ladder that wobbles, or that leans to the left or right.
11. When using a straight ladder, extend the top of the ladder at least 3 feet above the edge of the landing.
12. Do not move a rolling ladder while someone is on it.
13. Do not place ladders on barrels, boxes, loose bricks, pails, concrete blocks, or other unstable bases.
14. Do not carry items in your hands while climbing up or down a ladder.
15. Do not try to "walk" a ladder by rocking it. Climb down the ladder, and then move it.
16. Do not use a ladder as a horizontal platform.

LIFTING PROCEDURES

1. Plan the move before lifting; remove obstructions from your chosen pathway.
2. Test the weight of the load before lifting by pushing the load along its resting surface.
3. If the load is too heavy or bulky, use lifting and carrying aids such as hand trucks, dollies, pallet jacks and carts or get assistance from a co-worker.

4. If assistance is required to perform a lift, coordinate and communicate your movements with those of your co-worker.
5. Position your feet 6 to 12 inches apart with one foot slightly in front of the other.
6. Face the load.
7. Bend at the knees, not at the back.
8. Keep your back straight.
9. Get a firm grip on the object with your hands and fingers. Use handles when present.
10. Never lift anything if your hands are greasy or wet.
11. Wear protective gloves when lifting objects with sharp corners or jagged edges.
12. Hold objects as close to your body as possible.
13. Perform lifting movements smoothly and gradually; do not jerk the load.
14. If you must change direction while lifting or carrying the load, pivot your feet and turn your entire body. Do not twist at the waist.
15. Set down objects in the same manner as you picked them up, except in reverse.
16. Do not lift an object from the floor to a level above your waist in one motion. Set the load down on a table or bench and then adjust your grip before lifting it higher.
17. Slide materials to the end of the tailgate before attempting to lift them off a pick-up truck. Do not lift over the walls or tailgate of the truck bed.

PERSONAL PROTECTIVE EQUIPMENT

1. Do not paint or drill holes in hard hats.
2. Do not wear hard hats that are dented or cracked.
3. Wear safety glasses, goggles, or face shield when using chippers, grinders, lathes, or sanders.
4. Wear earplugs or earmuffs in areas posted "Hearing Protection Required."

GRINDING, BUFFING, AND SURFACE FINISHING PERSONNEL

Housekeeping

1. Do not place material such as paint containers or trash in walkways and passageways.
2. Do not use gasoline for cleaning purposes.
3. Keep floors clear of items such as metal chips, oily rags, metal shavings or metal dust.
4. Do not throw matches, cigarettes or other smoking materials into trash baskets.
5. Store rags that have oil or paint on them in closed metal containers labeled "oily rags."
6. Close the lids of containers of paint and thinner tightly after each use or when not being used.
7. Sweep up shavings from around equipment such as grinders, buffers or sanders by using a broom and a dustpan.

Machine/Equipment Safety

General

1. Read and obey safety warnings posted on or near any machine or piece of equipment.
2. Do not remove, alter or bypass any safety guards or devices when operating any piece of equipment or machinery.
3. Replace the guards before starting machines such as polishers, buffers or grinders or after making adjustments or repairs.
4. Long hair must be contained under a hat or hair net, regardless of gender.

Grinders

1. Do not use grinding wheels that have chips, cracks or grooves.
2. Do not use the grinding wheel if it wobbles. Tag it "Out of Service."
3. Adjust the tongue guard so that it is no more than 1/4 inch from the grinding wheel.
4. Do not try to stop the wheel with your hand, even if you are wearing gloves.
5. Do not perform metal grinding within 50 feet of containers labeled "Flammable" or "Combustible."

Buffers

1. Wear your face shield or safety goggles when operating the buffer. Do not wear gloves.
2. Before changing the buffing pad, turn the power switch of the buffer to "Off" and unplug it from the power source.
3. Keep your hands away from the rotating buffing pad.

Lockout/Tag out

1. Do not remove a lock from equipment unless you placed it there.
2. Attach your own lock or tag when you need to isolate an energy source.

Electrical Powered Tools

1. Do not use power equipment or tools on which you have not been trained.
2. Keep power cords away from path of grinders and buffers.
3. Do not use cords that have splices, exposed wires or cracked or frayed ends.
4. Do not carry plugged in equipment or tools with your finger on the switch.
5. Turn the tool off before plugging or unplugging it.
6. Do not leave tools that are "On" unattended.
7. Do not handle or operate electrical tools when your hands are wet or when you are standing on wet floors.
8. Do not operate spark inducing tools such as grinders near containers labeled "Flammable" or in an explosive atmosphere such as a paint spray booth.
9. Do not use extension cords or other grounded three-pronged power cords that have the ground prong removed or broken off.
10. Do not use an adapter that eliminates the ground such as a cheater plug.
11. Do not connect multiple electrical tools into a single outlet.
12. Do not use a power hand tool while wearing wet cotton gloves or wet leather gloves.
13. Do not operate power hand tools or portable appliances that have a frayed, worn, cut, improperly spliced or damaged power cord.
14. Do not operate power hand tools or portable appliances if the ground pin from the three-pronged power plug is missing or has been removed.
15. Do not operate power hand tools or portable appliances with a two-pronged adapter or a two-conductor extension cord.
16. Do not operate power hand tools or portable appliances while holding a part of the metal casing or holding the extension cord in your hand. Hold all portable power tools by the plastic hand grip or other nonconductive areas designed for gripping purposes.

Hydraulic/Pneumatic Tools

General

1. Do not use tools that have handles with burrs or cracks.
2. Do not use compressors if their belt guards are missing. Replace belt guards before use.
3. Turn the tool "off" and let it come to a complete stop before leaving it unattended.
4. Disconnect the tool from the air line before making any adjustments or repairs to the tool.
5. Do not point a compressed air hose at bystanders or use it to clean your clothing.

Pneumatic Sanding Equipment

1. Wear gloves, aprons, dust masks, goggles and hearing protection.
2. When using a disk sander, sand on the downward side of the disk.
3. Do not use your hands to hold the part to be sanded. Use clamps and fixtures.
4. Do not eat, drink, or use tobacco products while using sanders.
5. After leaving the sanding area wash hands and exposed skin surfaces of arms.

Blasting Equipment

1. Only blasters may use blasting equipment.
2. Visually inspect hoses or fittings on blasting equipment for wear and tear prior to use. Do not use if the hose or fitting is cracked or otherwise damaged.
3. Do not use compressed air to clean equipment or yourself.

Compressed Gas Cylinders**Storage and Handling**

1. Do not handle oxygen cylinders if your gloves are greasy or oily.
2. Store all cylinders in the upright position.
3. Do not lift cylinders by the valve protection cap.
4. Place valve protection caps on gas cylinders that are in storage or not in use.
5. Do not store compressed gas cylinders in areas where they can come in contact with chemicals labeled "Corrosive."
6. Place cylinders on a cradle, sling board, pallet or cylinder basket to hoist them.
7. Do not place cylinders against electrical panels or live electrical cords where the cylinder can become part of the circuit.

Use of Cylinders

1. Do not use dented, cracked or other visually damaged cylinders.
2. Use only an open ended or adjustable wrench when connecting or disconnecting regulators and fittings.
3. Do not transport cylinders without first removing regulators and replacing the valve protection caps.
4. Close the cylinder valve when work is finished, when the cylinder is empty or at any time the cylinder is moved.
5. Do not store oxygen cylinders near fuel gas cylinders such as propane or acetylene, or near combustible material such as oil or grease.
6. Stand to the side of the regulator when opening the valve.
7. If a cylinder is leaking around a valve or a fuse plug, move it to an outside area away from where work is performed and tag it to indicate the defect.
8. Do not hoist or transport cylinders by means of magnets or choker slings.
9. Do not remove the valve wrench from acetylene cylinders while the cylinder is in use.
10. Open compressed gas cylinder valves slowly. Open fully when in use to eliminate possible leakage around the cylinder valve stem.
11. Purge oxygen valves, regulators and lines before use.

Knives/Sharp Instruments

1. When handling snips, blades and other cutting tools, direct sharp points and edges away from you.
2. Cut in the direction away from your body when using knives.
3. Store knives in knife blocks or in sheaths after use.
4. Do not use knives with dull blades.
5. Do not use knives with broken or loose handles.
6. Do not use knives as screwdrivers or pry bars.
7. Do not carry knives, scissors or other sharp tools in pockets or aprons unless they are first placed in their sheath or holder.

General Hand Tool Safety

1. Use tied off containers to keep tools from falling off of elevated work platforms.
2. Tag worn, damaged or defective tools "Out of Service" and do not use them.
3. Do not use a tool if its handle has splinters, burrs, cracks, splits or if the head of the tool is loose.
4. Do not use impact tools such as hammers or chisels that have mushroomed heads.
5. When handing a tool to another person, direct sharp points and cutting edges away from yourself and the other person.
6. Do not carry sharp or pointed hand tools such as screwdrivers, scribes, snips, scrapers, chisels or files in your pocket unless the tool or pocket is sheathed.
7. Do not perform "make-shift" repairs to tools.

8. Do not carry tools in your hand when climbing. Carry tools in tool belts or hoist the tools to the work area with a hand line.
9. Do not throw tools from one location to another or from one employee to another.
10. Transport hand tools only in toolboxes or tool belts. Do not carry tools in your clothing.

Files/Rasps

1. When using a file or a rasp, grasp the handle in one hand and the toe of the file in the other.
2. Clean the grooves of a file with a wire brush.
3. Do not hammer on a file.

Chisels

1. Keep the cutting edge of the chisel sharp.
2. Hold a chisel with a tool holder if possible.
3. Clamp a small work piece in a vise and chip towards the stationary jaw when working with a chisel.

Hammers

1. Do not strike nails or other objects with the cheek of the hammer.
2. Do not strike a hardened steel surface, such as a cold chisel, with a claw hammer.
3. Do not use a hammer if your hands are oily, greasy or wet.

Painting Safety

1. Spray paint operators must use respirators provided by their supervisor for their assigned duties.
2. Wear goggles, gloves, face shields, long sleeve shirts and long pants when spray painting is being performed.
3. Always wash your hands with soap and water after using paints; Do not use mineral spirits, paint thinner, acetone or any other toxic solvents to remove paint from your skin.
4. Press the pressure relief valve on painting canisters and painting guns prior to disconnecting them.
5. Do not store food or eat where spray painting is being performed.
6. Close the lids of containers of paint and thinner tightly after each use or when not being used.

Hazardous Materials

1. Follow the instructions on the label and in the corresponding Material Safety Data Sheet (MSDS) for polishes and finishes used in your workplace.
2. Use personal protective clothing or equipment such as neoprene gloves, rubber boots, shoe covers, rubber aprons, and protective eyewear, when using chemicals labeled "Flammable," "Corrosive," "Caustic" or "Poisonous."
3. Do not use chemicals from unlabeled containers and unmarked cylinders.
4. Do not store chemical containers labeled "Oxidizer" with containers labeled "Corrosive" or "Caustic."
5. Only dispense a liquid labeled "Flammable" from its bulk container located in areas posted "Flammable Liquid Storage."
6. Each time you use your gloves, wash your gloves before removing them using cold tap water and normal hand washing motion. Always wash your hands after removing the gloves.

Personal Protective Equipment

1. Wear safety glasses such as grinding goggles or face shields when operating grinders or sanders.
2. Wear face shields over goggles or safety glasses during spray painting and metal plating operations.
3. Wear chemical goggles when using, applying or handling chemical liquids or powders from containers labeled "CAUSTIC" or "CORROSIVE."
4. Do not continue to work if your safety glasses become fogged. Stop work and clean the glasses until the lenses are clear and defogged.
5. Wear ear plugs or ear muffs in areas posted "Hearing Protection Required."
7. Spray paint operators must use respirators provided by their supervisor for their assigned duties.

Respirators

1. Shave daily to prevent facial hair from interfering with the face seal of the respirator.

2. Do not wear contact lenses when wearing a respirator.
3. Return respirators to their carrying cases or cartons and store them in your locker or in the storage area when the work is completed.
4. Only use the respirator that has been issued to you.

DRIVING/VEHICLE SAFETY

Fueling Vehicles

1. Turn the vehicle off before fueling.
2. Do not smoke while fueling a vehicle.
3. Wash hands with soap and water if you spill gasoline on your hands.

Driving Rules

1. Shut all doors and fasten your seat belt before moving the vehicle.
2. Obey all traffic patterns and signs at all times.
3. Maintain a three-point contact using both hands and one foot or both feet and one hand when climbing into and out of vehicles.

Vehicle Safety

1. Set the parking brake and use wheel blocks to chock the wheels of the truck before removing any metal work from the truck bed.
2. Secure metal work to the vehicle with chains or straps to eliminate or minimize shifting of the load.
3. No one is permitted to ride in trailers or truck beds.
4. Take slow, wide turns when towing trailers.
5. Do not exceed the load capacity as posted on door of the truck or trailer.
6. Do not place all the heavy metal parts on one side of the truck or trailer.
7. When using a belt driven conveyor to load metal parts onto a truck or trailer bed, the person inside the truck or trailer shall give verbal commands to the person loading the conveyor.
8. Do not ride on any conveyors.

Exposure Control Plan Access

Employees shall have access to a copy of the exposure control plan by request from their supervisor or the safety manager who will supply it in a reasonable time, place and manner.

Procedure Reviews and Updates

The exposure control procedure must be reviewed on an annual basis and updated whenever a new procedure, activity or function with the potential to expose employees to biohazards is introduced into a worksite.

Universal Precautions

Your employees shall observe universal precautions by treating all human blood and certain human body fluids as if they are known to be infectious for HIV, HBV and other pathogens even under circumstances where exposure is highly unlikely.

Exposure Controls

Exposure controls are designed to reduce or eliminate employee exposure to blood or potentially infectious materials and should be re-evaluated and revised if necessary, on a regular basis to maximize their effectiveness in controlling employee exposure. Therefore:

- Hand washing facilities are readily available at all work locations except those that cannot support or simply do not have such facilities. In these cases, appropriate antiseptic solutions and / or towelettes are available for use.
- All sharps' containers shall have a biohazard-warning label or a specific color to identify it as a biohazard, shall be resistant to punctures and shall be leak proof. The same characteristics shall apply to all secondary sharps' containers.

Safe Work Practices

Safe work practices are designed to support exposure controls and further minimize or eliminate occupational exposure. Therefore:

- Employees must wash hands and other applicable body parts as soon as potentially contaminated gloves or other PPE are removed to further prevent contamination.
- If any part of the body has contact with blood or any other infectious material, employees must wash hands and other exposed body parts with soap and water immediately.
- Only trained and authorized personnel are allowed to handle sharps, sharps containers and any other potentially sharp and infectious needles or equipment.
- Activities such as applying make up, handling contact lenses, smoking or any other hand and eye, mouth, nose, ear or other body part contact is prohibited in areas where exposure to biohazards is possible.
- Storage areas such as pantries, freezers, refrigerators and others that may contain potentially infectious materials shall not contain food or drink.
- All equipment and surfaces that have had contact with blood or other infectious materials must be properly cleaned and decontaminated.
- All biological specimens must be contained in leak proof containers for handling, storage and transport to minimize potential contact with other surfaces and employees.
- In cases where the exterior surface of the specimen container is contaminated; the container must be placed into another leak proof container, which shall be labeled as "for handling and storage".

- All emergency responder, first aid or other potentially infectious supplies must be disposed of immediately and appropriately after contamination.

Personal Protective Equipment (PPE)

PPE shall be provided by your company at no cost to the employee and must be of proper fit, adequate for the task at hand and readily available. Defective or damaged PPE must be discarded / replaced or repaired in order to ensure maximum effectiveness.

The following safe work practices shall be followed with regard to biohazards and PPE:

- Protective garments that are penetrated by blood or other infectious materials must be removed and properly disposed of immediately.
- PPE that may be contaminated must be removed and properly stored / contained before leaving the work area.
- PPE such as protective gloves must be worn whenever contact with potentially infectious material exposure is anticipated.
- Disposable PPE such as rubber gloves must be replaced as soon as practical when contamination has occurred or when they are rendered ineffective by a tear, puncture or other occurrence.
- Masks and eye protection (such as goggles, face shields, etc.) are used whenever splashes or sprays may generate droplets of infectious materials.
- Whenever infectious material splashes, sprays or other similar occurrences are possible, PPE such as face shields, goggles, head garments or other appropriate PPE shall be used to protect face, eyes etc.
- Adequate PPE must be used unless temporarily declined by the employee and approved by the safety manager.
- PPE should be cleaned, laundered & properly disposed of if contaminated.
- All PPE must be cleaned, maintained, used, stored and disposed of properly when applicable.

Post-Exposure Requirements

All potential blood or infectious material exposure incidents shall be investigated by the employer thoroughly to ensure that hazards are abated and that affected employees receive the necessary treatment needed to minimize the impact of potential or actual exposure.

All reported exposure incidents shall be formally investigated by the exposure control officer / safety manager or supervisor when the safety manager cannot be present. A detailed report of the incident outlining root cause, corrective actions and the current status of affected employees is then completed and reviewed by employer to help prevent re-occurrence. Additionally, the following confidential information shall be provided to exposed employees:

- All documentary reports and information of the exposure incident and its circumstances.
- The identity of the exposure source individual unless applicable laws prevent such identification.

Upon completion of the above procedures, the exposed employee shall be appointed to a qualified healthcare professional who will evaluate the exposed employee, provide information to the employee about his or her medical status and initiate treatment where applicable.

Employer shall provide the following information to the healthcare professional:

- A copy of the biohazard's standard.

- A detailed description of the exposure incident.
- Additional information that is relevant to the healthcare professional.

The following information will be provided to the employer by the healthcare professional as a “written report” and copied to the exposed employee upon completion of the healthcare professional’s evaluation of exposed employee:

- If a Hepatitis B vaccination is recommended for the exposed employee.
- If the exposed employee has received the Hepatitis B vaccination since the incident.
- Verification that the exposed employee has received results information of the medical evaluation.
- Verification that the exposed employee was made aware of medical conditions caused by the exposure incident that require additional medical evaluation or treatment.

* All other medical information remains confidential and will not be a part of the written report.

* The Hepatitis B vaccine will be made available to all employees with occupational exposure at no cost.

HEAT ILLNESS AND PREVENTION

All managers and supervisors will implement and maintain the Heat Illness Program in their respective work areas. High heat procedures are to be followed when the temperature exceeds 80 degrees Fahrenheit. High heat procedures shall include, but are not limited to:

- Effective communication by voice, observation or electronic means,
- Will observe employees for alertness and signs/symptoms of heat illness often,
- Reminding employees to drink water throughout the shift,
- Closely supervise new employees for their first 14 days of employment,
- The provisions of this procedure.

Provision of Water

Employees shall have access to potable drinking water. Where it is not plumbed or otherwise continuously supplied, it shall be provided in sufficient quantity at the beginning of the work shift.

Access to Shade

Employees must have access to shade. At or below 80 degrees Fahrenheit the employee shall have timely access to shade upon request. For temperatures at or above 80 degrees Fahrenheit, one or more areas with shade shall be provided at all times while employees are present. There should be enough shade for at least 25% of employees on the shift at any one time to use.

Employees suffering from heat illness or those who believe a preventative recovery period is needed shall be provided access to an area with shade that is either open to the air or provided with ventilation or cooling for a period of no less than five minutes. Such access to shade shall be permitted at all times. See definition of "Shade".

Written Procedures

The heat prevention program/procedures shall be in writing and shall be made available to employees.

Each work site shall develop site-specific procedures, which shall include the minimum:

- Make available at least 2 quarts of water per employee at the start of the shift. The supervisors or designated persons will monitor water containers every 30 minutes. Employees are encouraged to report to the supervisor/designated person water that is dirty or an inadequate water supply.
- Supervisors will provide frequent reminders to employees to drink frequently.
- Workers will be reminded every morning of the importance of frequent consumption of water throughout the shift during hot weather.
- Place water containers as close as possible to the workers.
- Water levels should not fall below the point that will provide adequate water for all employees during the time necessary to effect replenishment.
- Disposable/single use drinking cups will be provided to employees or provisions will be made to supply employees their own cups.
- Supervisors will set-up an adequate number of umbrellas, canopies or other portable devices at the start of the shift and will relocate them to be closer to the crew, as needed.

- Non-agricultural employers can use other cooling measures if they demonstrate that these methods are as effective as shade.

Working hours will be modified to work during the cooler hours of the day, when possible.

More water and rest breaks will be provided when a modified or shorter work-shift is not possible.

Supervisors will continuously monitor all employees and stay alert to the presence of heat related symptoms.

Supervisors will carry cell phones or other means of communication, to ensure that emergency services can be called.

They will check that all means of communication are functional at the worksite prior to each shift.

Every morning, workers will be reminded about the address and directions to their worksite so as to inform medical responders.

All newly hired workers will be assigned a buddy or experienced coworker to ensure they receive proper training and are following the company procedures in regard to heat illness prevention.

General Requirements

When work cannot be performed safely from the ground, or from solid construction, scaffolds must be supplied and erected according to the applicable standards for the employees involved. In the case that ladders are used, the work must conform to ladder safety standards.

Scaffolds must be erected by a qualified individual (someone who can certify that the scaffolding is safe to use).

Scaffolds must be set on footings or anchored to material that is sound, rigid, and able to support the maximum intended load without settling or shifting. Never use unstable objects such as loose boards, barrels, or boxes to support scaffolds or planks.

Only use scaffolds (and components) that are capable supporting (without failure) at least four times the maximum intended load. All scaffold components must comply with OSHA requirements 29 CFR 1910.28 and 29 CFR 1926.451.

If using wood scaffold planks, they must be cross-supported every 8 feet. Cleat, wire or nail scaffold deck boards into place.

You must completely floor all working levels of scaffolds except where space is required for openings for internal ladders.

Maintenance of scaffolds and other components described in this program is required to keep them in safe condition. Never alter or move (horizontally) a scaffold that is occupied.

Immediately repair any damaged or weakened scaffold. Never use a damaged or weakened scaffold until repairs have been completed.

Never load a scaffold in excess of the working load that it is intended for.

Always use properly sized bolts in the construction of scaffolds and use sufficient number at each connection to create the designed strength of the scaffold.

Always overlap platforms (minimum of 12 inches) and secure them from any movement.

Always provide an access ladder or equivalent safe access.

Always extend scaffold planks over their end supports by not less than 6 inches and not more than 18 inches.

Ensure that poles, legs, and uprights of scaffolds are plumb, and are rigidly braced and secured to prevent swaying and shifting.

Always apply a tag line to materials being hoisted onto a scaffold.

Always provide overhead protection workers on a scaffold if they are exposed to overhead hazards.

If a scaffold or platform is erected over 6 feet off the ground, always install toe boards and guardrails. Where workers are required to work or pass under the scaffold, always install a screen between the toe board and the guardrail (along the entire opening), consisting of No. 18 gauge wire one-half inch mesh or the equivalent.

Never perform work on a scaffold during storms or high winds.

Never perform work on a scaffold that is covered with snow or ice, unless all the snow and ice is removed, and planking is

sanded to prevent slipping.

Do not accumulate tools, material, and debris on a scaffold such that it presents a hazard.

Inspections

A qualified individual as per the manufacturer's recommendations must inspect scaffolding. The qualified individual must also conduct inspections prior to each use and periodically throughout each shift.

- A qualified individual inspects the scaffold after it is erected, prior to the start of the workday, and at the beginning of a shift change to ensure the scaffold is safe prior to and during use. At a minimum, the following shall be inspected:
 - Ensure there is no settling in the ground or surface footing.
 - Check for any signs of damage, missing pins, bolts and any locks and/or safety keepers on all main supports and cross braces.
 - Check for damage, proper placement and any possible movement of all walking surfaces and/or planks.
 - Check that all walkways and planks are secure to prevent movement.
- The inspection will ensure that the scaffold is stable, and movement is prevented.
- If a defect or damage to the scaffold is discovered during the inspection, the qualified individual must tag the scaffold out. Use of the scaffold will be prohibited until the necessary repairs are made.

Mandatory Signs and Tags

Signs and tags must be visible at all times when performing work and must be promptly removed or covered when the hazard are abated. Tags shall also be used when defective equipment or unsafe conditions are found.

The qualified individual will tag out any defective or unsafe equipment or conditions (e.g., improper footings) shall using a weather resistant tag that is secured to the scaffolding structure on all four sides.

Only use danger signs where an immediate hazard exists. To alert other workers of possible danger from falling objects, post danger signs in the immediate area of the scaffold.

Caution - To mark off a larger area around scaffolding and warn other workers to use caution, use signs and/or barricade tape.

Modifications

A qualified person must perform all modifications and repairs. This qualified person must be able to certify that the scaffolding is safe to use to ensure that non-qualified personnel do not create additional hazards.

Only employees who are trained and certified shall perform modifications or repairs. Unqualified employees who fail to comply may receive disciplinary action and or termination.

HAZARD IDENTIFICATION AND ASSESSMENT

To assist in the identification and correction of hazards, the company has developed the following procedures. These procedures are representative only and are not exhaustive of all the measures and methods that will be implemented to guard against injury from recognized and potential hazards in the workplace. As new hazards are identified or improved work procedures developed, they will be promptly incorporated into our Safety Manual. The following methods will be utilized to identify hazards in the workplace:

- Loss analysis of accident trends
- Accident investigation
- Employee observation
- Employee suggestions
- Regulatory requirements for our industry
- Outside agencies such as the fire department and insurance carriers
- Periodic safety inspections

Loss Analysis

Periodic loss analyses will be conducted by the safety program administrator. These will help identify areas of concern and potential job hazards. The results of these analyses will be communicated to management, supervision, and employees through safety meetings and other appropriate means.

Accident Investigations

All accidents and injuries will be investigated in accordance with the guidelines contained in this program. Accident investigations will focus on all causal factors and corrective action including the identification and correction of hazards that may have contributed to the accident.

Employee Observation

Superintendents and foremen shall be continually observing employees for unsafe actions and taking corrective action as necessary.

Employee Suggestions

Employees are encouraged to report any hazard they observe to their supervisor. No employee is to ever be disciplined or discharged for reporting any workplace hazard or unsafe condition. However, employees who do NOT report potential hazards or unsafe conditions that they are aware of will be subject to disciplinary action.

All industries are subject to government regulations relating to safety. Many of these regulations are specific to our type of business. Copies of pertinent regulations can be obtained from the Safety Program Administrator.

Outside Agencies

Several organizations may assist us in identifying hazards in our workplace. These include safety officers from other contractors, insurance carrier safety and health consultants, private industry consultants, the fire department, and State OSH Consultants.

Periodic Safety Inspections

Periodic safety inspections ensure that physical and mechanical hazards are under control and identify situations that may become potentially hazardous. Inspections shall include a review of the work habits of employees in all work areas. These inspections will be conducted by the Supervisor, Manager, Program Administrator or other designated individual.

Periodic safety inspections will be conducted:

- When new substances, process, procedures or equipment are used.
- When new or previously unrecognized hazards are identified.
- Periodically by the Supervisor.
- Periodically by the Safety Program Administrator.

These inspections will focus on both unsafe employee actions as well as unsafe conditions. The following is a partial list of items to be checked.

- The proper use, condition, maintenance and grounding of all electrically operated equipment.
- The proper use, condition, and maintenance of safeguards for all power-driven equipment.
- Compliance with the Code of Safe Practices.
- Housekeeping and personal protective equipment.
- Hazardous materials.
- Proper material storage.
- Provision of first aid equipment and emergency medical services.

Any and all hazards identified will be corrected as soon as practical in accordance with the company hazard correction policy.

If imminent or life-threatening hazards are identified, which cannot be immediately corrected, all employees must be removed from the area, except those with special training required to correct the hazard, who will be provided necessary safeguards.

Documentation of Inspections

Safety inspections will be documented to include the following:

- Date on which the inspection was performed.
- The name and title of person who performed the inspection.
- Any hazardous conditions noted or discovered, and the steps or procedures taken to correct them.

- Signature of the person who performed the inspection.

One copy of the completed form should be sent to the office. All reports shall be kept on file for a minimum of two (2) years.

HAZARD PREVENTION, CORRECTION, AND CONTROL

The following procedures will be used to evaluate, prioritize and correct identified safety hazards. Hazards will be corrected in order of priority: the most serious hazards will be corrected first.

Hazard Evaluation

Factors that will be considered when evaluating hazards include:

- Potential severity - The potential for serious injury, illness or fatality
- Likelihood of exposure - The probability of the employee coming into contact with the hazard
- Frequency of exposure - How often employees come into contact with the hazard
- Number of employees exposed
- Possible corrective actions - What can be done to minimize or eliminate the hazard
- Time necessary to correct - The time necessary to minimize or eliminate the hazard

Techniques for Correcting Hazards

1. Engineering Controls: Could include machine guarding, ventilation, noise reduction at the source, and provision of material handling equipment. These are the first and preferred methods of control.
2. Administrative Controls: The next most desirable method would include rotation of employees or limiting exposure time.
3. Personal Protective Equipment: Includes back support belts, hearing protection, respirators and safety glasses. These are often the least effective controls for hazards and should be relied upon only when other controls are impractical.

Documentation of Corrective Action

All corrective action taken to mitigate hazards should be documented. Depending on the circumstances, one of the following forms should be used:

- Safety Contact Report
- Safety Meeting Report
- Memo or letter
- Safety inspection form

All hazards noted on safety inspections will be rechecked on each subsequent inspection and notations made as to their status.

Introduction

It is company policy that the first consideration of work shall be the protection of the safety and health of all employees. We have developed this Hazard Communication Program to ensure that all employees receive adequate information about the possible hazards that may result from the various materials used in our operations. This Hazard Communication Program will be monitored by the Safety Program Administrator who will be responsible for ensuring that all facets of the program are carried out, and that the program is effective.

Our program consists of the following elements:

1. Hazardous material inventory.
2. Collection and maintenance of Material Safety Data Sheets.
3. Container labeling.
4. Employee training.

The following items are not required to be included in the program and are therefore omitted:

- Foods, drugs, cosmetics or tobacco.
- Untreated wood products.
- Hazardous waste.
- Consumer products packaged for sale to and use by the general public, provided that our exposure is not significantly greater than typical consumer exposure.

Hazardous Material Inventory

The Safety Program Administrator maintains a list of all hazardous materials used in our operations. This list contains the name of the product, the type of product (solvent, adhesive etc.) and the name and address of the manufacturer.

Material Safety Data Sheets (MSDS)

Copies of MSDS for all hazardous substances to which our employees may be exposed will be kept in a binder at the main office. These MSDS are available to all employees, at all times, upon request. The Supervisor at the work site will also keep copies of the most commonly used products.

The Safety Program Administrator will be responsible for reviewing incoming MSDS for new and significant health/safety information. They will ensure that any new information is passed on to the affected employees.

The Safety Program Administrator will also review all incoming MSDS for completeness. If an MSDS is missing or obviously incomplete, a new MSDS will be requested from the manufacturer. Federal or State (if applicable) OSHA will be notified if a complete MSDS is not received, and the manufacturer will not supply one.

New materials will not be introduced into the shop or field until a MSDS has been received. The purchasing department will make it an ongoing part of their function to obtain MSDS for all new materials when they are first ordered.

Container Labeling

No container of hazardous substances will be used unless the container is correctly labeled and the label is legible.

All chemicals in cans, bags, drums, pails, etc., will be checked by the receiving department to ensure the manufacturer's label is intact, is legible, and has not been damaged in any manner during shipment. Any containers found to have damaged labels will be held until a new label has been installed. New labels will be obtained from the manufacturer.

The label must contain:

- The chemical name of the contents.
- The appropriate hazard warnings.
- The name and address of the manufacturer.

All secondary containers will be labeled as to their contents with a reference to the original label.

Employee Information and Training

All employees will be provided information and training on the following items through the company safety training program and prior to starting work with hazardous substances:

1. An overview of the requirements of the Hazard Communication Standard, including their rights under this regulation.
2. Information regarding the use of hazardous substances in their specific work areas.
3. The location and availability of the written hazard communication program. The program will be available from the Supervisor and Safety Program Administrator.
4. The physical and health hazards of the hazardous substances in use.
5. Methods and observation techniques used to determine the presence or release of hazardous substances in the work area.
6. The controls, work practices and personal protective equipment available for protection against possible exposure.
7. Emergency and first aid procedures to follow if employees are exposed to hazardous substances.
8. How to read labels and material safety data sheets to obtain the appropriate hazard information.

Hazardous Non-Routine Tasks

Infrequently, employees may be required to perform hazardous non-routine tasks. Prior to starting this work, each involved employee will be given information by his/her supervisor about hazards to which they may be exposed during such activity.

This information will include:

- The specific hazards.
- Protective/safety measures which must be utilized.
- The measures the company has taken to lessen the hazards, including special ventilation, respirators, the presence of another employee, emergency procedures, etc.

Informing Outside Contractors and Vendors

To ensure that outside contractors are not exposed to our hazardous materials, and to ensure the safety of the contractor's

employees, it will be the responsibility of the Supervisor to provide outside contractors the following information:

- The hazardous substances under our control that they may be exposed to while at the work site.
- The precautions the contractor's employees must take to lessen the possibility of exposure.

We will obtain from outside contractors and vendors the name of any hazardous substances the contractor's employees may be using at a work site or bringing into our facility. The contractor must also supply a copy of the material safety data sheet relevant to these materials.

Employee Rights Under The Hazard Communication Standard

At any time, an employee has the right to:

- Access the MSDS folder, and the Hazard Communication Program.
- Receive a copy of any environmental sampling data collected in the workplace.
- See their employment medical records upon request.

FIRST AID AND MEDICAL EMERGENCY PROCEDURES

The company will ensure the availability of emergency medical services for its employees at all times. We will also ensure the availability of a suitable number of appropriately trained persons to render first aid. The Safety Program Administrator will maintain a list of trained individuals and take steps to provide training for those that desire it.

First-Aid Kits

Every work site shall have access to at least one first-aid kit in a weatherproof container. The first-aid kit will be inspected regularly to ensure that it is well stocked, in sanitary condition, and any used items are promptly replaced. The contents of the first-aid kit shall be arranged to be quickly found and remain sanitary. First-aid dressings shall be sterile and in individually sealed packages.

Drugs, antiseptics, eye irrigation solutions, inhalants, medicines, or proprietary preparations shall not be included in first-aid kits unless specifically approved, in writing, by an employer-authorized, licensed physician. Other supplies and equipment, if provided, shall be in accordance with the documented recommendations of an employer-authorized licensed physician upon consideration of the extent and type of emergency care to be given based upon the anticipated incidence and nature of injuries and illnesses and availability of transportation to medical care.

First Aid

The designated first aid person on each site will be available at all times to render appropriate first aid for injuries and illnesses. Proper equipment for the prompt transportation of the injured or ill person to a physician or hospital where emergency care is provided, or an effective communication system for contacting hospitals or other emergency medical facilities, physicians, ambulance and fire services, shall also be provided. The telephone numbers of the following emergency services in the area shall be posted near the job telephone, or otherwise made available to the employees where no job site telephone exists:

1. A company authorized physician or medical clinic, and at least one alternate if available.
2. Hospitals.
3. Ambulance services.
4. Fire-protection services.

Prior to the commencement of work at any site, the Supervisor or Manager shall locate the nearest preferred medical facility and establish that transportation or communication methods are available in the event of an employee injury.

Each employee shall be informed of the procedures to follow in case of injury or illness through our new employee orientation program, Code of Safe Practices, and safety meetings.

Where the eyes or body of any person may be exposed to injurious or corrosive materials, suitable facilities for drenching the body or flushing the eyes with clean water shall be conspicuously and readily accessible.

Accident Procedures

These procedures are to be followed in the event of an employee injury in the course of employment.

1. For severe accidents call 911 and request the Paramedics.
2. Employees must report all work-related injuries to their Supervisor immediately. Even if they do not feel that it requires medical attention. Failure to do so may result in a delay of Workers' Compensation benefits and disciplinary action.
3. The Supervisor, employee, and first aid person, should determine whether or not outside medical attention is needed. When uncertainty exists on the part of any individual, the employee should be sent for professional medical care.
4. If medical attention is not desired or the employee refuses treatment, you must still fill out a company "Accident Report" in case complications arise later.
5. In all cases, if the employee cannot transport himself or herself for any reason, transportation should be provided.
6. In the event of a serious accident involving hospitalization for more than 24 hours, amputation, permanent disfigurement, loss of consciousness or death, phone contact should be made with the main office. Contact must also be made with the nearest Federal or State (if applicable) OSHA office.

ACCIDENT / EXPOSURE INVESTIGATION

The Supervisor, Manager, or other designated individual will investigate all work-related accidents in a timely manner. This includes minor incidents and "near accidents", as well as serious injuries. An accident is defined as any unexpected occurrence that results in injury to personnel, damage to equipment, facilities, or material, or interruption of normal operations.

Responsibility for Accident Investigation

Immediately upon being notified of an accident, the Supervisor, Manager, or other designated individual shall conduct an investigation. The purpose of the investigation is to determine the cause of the accident and corrective action to prevent future reoccurrence; not to fix blame or find fault. An unbiased approach is necessary in order to obtain objective findings.

The Purpose of Accident Investigations:

- To prevent or decrease the likelihood of similar accidents.
- To identify and correct unsafe work practices and physical hazards. Accidents are often caused by a combination of these two factors.
- To identify training needs. This makes training more effective by focusing on factors that are most likely to cause accidents.

What Types of Incidents Do We Investigate?

- Fatalities
- Serious injuries
- Minor injuries
- Property damage
- Near misses

Procedures for Investigation of Accidents

Immediately upon being notified of an accident the Supervisor, Manager, or other designated individual will:

1. Visit the accident scene, as soon as possible, while facts and evidence are still fresh and before witnesses forget important details and to make sure hazardous conditions to which other employees or customers could be exposed are corrected or have been removed;
2. Provide for needed first aid or call 911 emergency for the injured employee(s).
3. If possible, interview the injured worker at the scene of the accident and verbally "walk" him or her through a re-enactment. All interviews should be conducted as privately as possible. Interview all witnesses individually and talk with anyone who has knowledge of the accident, even if they did not actually witness it.
4. Report the accident to the main office. Accidents will be reported by the office to the insurance carrier within 24 hours.

All serious accidents will be reported to the carrier as soon as possible.

5. Consider taking signed statements in cases where facts are unclear or there is an element of controversy.
6. Thoroughly investigate the accident to identify all accident causes and contributing factors. Document details graphically. Use sketches, diagrams and photos as needed. Take measurements when appropriate.
7. All accidents involving death, disfigurement, amputation, loss of consciousness or hospitalization for more than 24 hours must be reported to Federal or State (if applicable) OSHA immediately.
8. Focus on causes and hazards. Develop an analysis of what happened, how it happened, and how it could have been prevented. Determine what caused the accident itself, not just the injury.
9. Every investigation must also include an action plan. How can such accidents be prevented in the future?
10. In the event a third party or defective product contributed to the accident, save any evidence as it could be critical to the recovery of claim costs.

Accurate & Prompt Investigations

- Ensures information is available
- Causes can be quickly corrected
- Helps identify all contributing factors
- Reflects management concern
- Reduces chance of recurrence

Investigation Tips

- Avoid placing blame
- Document with photos and diagrams, if needed
- Be objective, get the facts
- Reconstruct the event
- Use open-ended questions

Questions to Ask

When investigating accidents, open-ended questions such as who? what? when? where? why?, and how? will provide more information than closed-ended questions such as "Were you wearing gloves?"

Examples include:

- How did it happen?
- Why did it happen?
- How could it have been prevented?
- Who was involved?
- Who witnessed the incident?
- Where were the witnesses at the time of the incident?
- What was the injured worker doing?
- What was the employee working on?
- When did it happen?

- When was the accident reported?
- Where did it happen?
- Why was the employee assigned to do the job?

The single, most important question that must be answered as the result of any investigation is:

"What do you recommend be done (or have you done) to prevent this type of incident from recurring?"

Once the Accident Investigation is Completed

- Take or recommend corrective action
- Document corrective action
- Management and the Safety Program Administrator will review the results of all investigations
- Consider safety program modifications

Information obtained through accident investigations can be used to update and improve our current program.

Every new employee will be given instruction by their supervisor in the general safety requirements of their job. A copy of our Code of Safe Practices shall also be provided to each employee.

Managers, Supervisors, and employees will be trained at least twice per year on various accident prevention topics.

Training provides the following benefits:

- Makes employees aware of job hazards
- Teaches employees to perform jobs safely
- Promotes two-way communication
- Encourages safety suggestions
- Creates interest in the safety program
- Fulfills Federal or State (if applicable) OSHA requirements

Employee training will be provided at the following times:

1. All new employees will receive a safety orientation their first day on the job.
2. All new employees will be given a copy of the Code of Safe Practices and required to read and sign for it.
3. All employees given a new job assignment for which training has not been previously provided will be trained before beginning the new assignment.
4. Whenever new substances, processes, procedures or equipment that represent a new hazard are introduced into the workplace.
5. Whenever the company is made aware of a new or previously unrecognized hazard.
6. Whenever management believes that additional training is necessary.
7. After all serious accidents.
8. When employees are not following safe work rules or procedures.

Training topics will include, but not be limited to:

- Employee's safety responsibility
- General safety rules
- Code of Safe Practices
- Safe job procedures
- Ergonomics
- Use of hazardous materials
- Use of equipment
- Emergency procedures
- Safe lifting and material handling practices
- Contents of safety program

All training will be documented on one of the following three forms.

New Employee Safety Orientation

Employee Safety Contact Form

Safety Meeting Report

The following training method should be used. Actual demonstrations of the proper way to perform a task are very helpful in most cases.

- Tell them how to do the job safely
- Show them how to do the job safely
- Have them tell you how to do the job safely
- Have them show you how to do the job safely

Follow up to ensure they are still performing the job safely

FIRE PREVENTION AND EMERGENCY ACTION PLAN

The company has developed the following emergency plan to cover those designated actions that must be taken to ensure employee safety from fire and during other emergencies. Any questions about this plan should be directed to The Safety Program Administrator.

Facility Emergency Evacuation and Fire Prevention

The Safety Program Administrator is responsible for ensuring the following:

1. That all required emergency exits are clearly identified in the office, shop, and warehouse and that all required fire fighting and emergency equipment is available and in good condition.

The following items will be maintained:

- First aid kit
 - Drinking water
 - Flashlight
 - Portable battery powered radio and batteries
 - Fire extinguishers
 - Wrench to shut off the main gas valve
 - Pry bars, axes, saws, tools or similar devices for employee rescue
2. Creating a facility map designating all emergency evacuation routes and the locations of all fire fighting equipment and emergency supplies and equipment. These maps will be posted in at least two locations in the facility.
 3. Training all exposed employees on the procedures to be followed in the event of fire, earthquake or other emergency including how to properly notify other affected employees.
 4. Identifying potential fire hazards in the office, shop and warehouse and ensuring that adequate steps are taken to prevent fires.
 5. Ensuring that combustible trash and materials are removed promptly from the facility, and that all flammable and combustible liquids are properly stored and handled.

During an Emergency

In the event of an emergency such as earthquake or fire, all employees are expected to evacuate the premises immediately. The Safety Program Manager or Safety Committee members may assign some employees the task of shutting off the gas or electricity, if needed. At no time will any employee be expected to jeopardize their own safety to do this.

Employees will be notified of emergencies through one of the following:

- Fire alarm
- Intercom
- Emergency horn
- Direct voice communication

After the emergency evacuation has been completed, a head count will be taken to ensure everyone is out of the building.

If necessary, the Safety Program Administrator or Safety Committee members may assign some employees to rescue trapped employees.

Fire Prevention in Shops and Warehouses

The following procedures will be used to prevent fires in shops and warehouses.

1. All accumulated combustible trash and debris will be removed as soon as practical.
2. Flammable liquids will only be stored and dispensed from UL approved safety containers designed for that purpose.
3. All rags soaked with flammable or combustible liquids will be properly stored in closed metal containers.
4. Appropriate precautions will be taken to prevent fires when torch cutting, welding or soldering.
5. Compressed gas cylinders containing flammable or explosive gasses will be properly stored in the upright position with their caps on and protected from heat or puncture. Fuel gas and oxygen shall be separated at least 20 feet when stored.
6. Smoking or open lights are prohibited within 50 feet of flammable liquid or gas storage and dispensing areas.
7. Flammable solvents will not be used for cleaning purposes.
8. A fire extinguisher, rated not less than 2A, shall be provided for each 3,000 square feet of the floor area, or fraction thereof. Where the floor area is less than 3,000 square feet, at least one extinguisher shall be provided.
9. Travel distance from any point of the protected area to the nearest fire extinguisher shall not exceed 75 feet.
10. At least one fire extinguisher, rated not less than 2A, shall be provided on each floor. In multi-story buildings, at least one fire extinguisher shall be located adjacent to the stairway at each floor level.
11. A fire extinguisher, rated not less than 10B, shall be provided within 50 feet of wherever more than 5 gallons of flammable or combustible liquids or 5 pounds of flammable gas are being used on the job site. This requirement does not apply to the integral fuel tanks of motor vehicles.
12. Portable fire extinguishers shall be inspected monthly, or at more frequent intervals by the employer, and serviced at least annually by a person licensed or registered by the State Fire Marshal. NOTE: Inspection is a "quick check" that an extinguisher is available and will operate. It is intended to give reasonable assurance that the extinguisher is fully charged and operable. This is done by seeing that it is in its designated place, that it has not been actuated or tampered with, and that there is no obvious or physical damage or condition to prevent operation.
13. Suitable fire control devices, such as portable fire extinguishers, shall be available at locations where flammable or combustible liquids are stored.
14. At least one portable fire extinguisher, having a rating of not less than 20-B units, shall be located outside of, but not more than 10 feet from, the door opening into any room used for flammable liquid storage.
15. At least one portable fire extinguisher, having a rating of not less than 20-B units, shall be located not less than 25 feet, nor more than 75 feet, from any flammable liquid storage area located outside.

FLEET AND DRIVER SAFETY

The company has established the following guidelines and procedures for our drivers and vehicles to protect the safety of individuals operating any motor vehicle on company business. Protecting our employee drivers, their passengers, and the public is of the highest priority. The commitment of management and employees is critical to the success of this program. Clear communication of, and strict adherence to, the program's guidelines and procedures are essential.

Our primary goal is to maintain a high level of safety awareness and foster responsible driving behavior. Driver safety awareness and responsible driving behavior will significantly decrease the frequency of motor vehicle accidents and reduce the severity of personal injuries and property damage.

Drivers must follow the requirements outlined in this program. Violations of this program may result in disciplinary action up to, and including, suspension of driving privileges or dismissal.

Our program consists of the following elements:

- Driver selection
- Driver training
- Vehicle use policy
- Vehicle inspection & preventive maintenance
- Accident investigation

Driver Selection

Only company authorized and assigned employees are allowed to drive company vehicles at any time. Prior to being authorized and assigned, the company will check the following items. Drivers must have:

- A valid un-restricted drivers license.
- A current MVR driving record with no more than 2 points and no serious or major violations.

The company will also check driving records of all employees authorized to drive on company business on an annual basis.

Employees that do not meet these requirements are not authorized or allowed to drive company vehicles or drive their own vehicle on company business.

Driver Training

All employees driving company vehicles, and personal vehicles on company business, will be given a copy of the Driving Safety Rules and Company Vehicle Use Policy and required to read and sign for them. Safe driving will also be periodically covered at company safety meetings.

Company Vehicle Use Policy

The company has established the following policies pertaining to company vehicles:

1. Personal and off duty use of company vehicles is prohibited.
2. Only authorized employees may drive company vehicles. No other family members may drive company vehicles.
3. Non-employee passengers are not permitted in company vehicles at any time, unless they are business related.
4. Seat belts must be worn in company vehicles at all times.
5. No employee is permitted to drive company vehicles while impaired by alcohol, illegal or prescription drugs, or over the counter medications.
6. All accidents involving company vehicles must be reported to the office immediately.
7. Employees with two or more preventable accidents in a three year period, or that obtain three points on their driving record, will be subject to a loss of their driving privileges or have their driving privileges restricted.

Vehicle Inspection & Preventive Maintenance

All company vehicles must be inspected by the driver prior to each use. Mechanical defects will be repaired immediately. The Safety Program Administrator will periodically spot check company vehicles to determine their condition.

Vehicle inspections will include:

- Lights
- Turn signals
- Emergency flashers
- Tires
- Horn
- Brakes
- Fluids
- Windshield condition and wiper condition
- Mirrors

All vehicles will also be maintained in accordance with the manufacturers' recommendations. It is the responsibility of the individual assigned the vehicle to ensure proper maintenance and repairs are performed. If your vehicle is not safe, do not drive.

Accident Investigation

All accidents in company vehicles will be investigated by the Supervisor, Manager and / or the Safety Program Administrator. Where possible, witness's statements will be obtained and photos used to document the scene of the accident and the damage. Police reports will also be obtained whenever possible. The following guidelines will be used to help determine preventability.

Auto Accident Preventability Guide

This guide will assist in determining whether our driver could have prevented the accident. An accident is preventable if the

driver could have done something to avoid it. Drivers are expected to drive defensively. Which driver was primarily at fault, which received a traffic citation, or whether a claim was paid has no bearing on preventability. If there was anything our driver could have done to avoid the collision, then the accident was preventable.

An accident was non preventable when the vehicle was legally and properly parked, or when properly stopped because of a highway patrol officer, a signal, stop sign, or traffic condition. When judging accident preventability, here are some general questions to consider:

1. Does the investigation indicate that the driver considers the rights of others, or is there evidence of poor driving habits that need to be changed?
2. Does the investigation indicate driver awareness? Such phrases as "I did not see," "I didn't think," "I didn't expect," or "I thought" are signals indicating there probably was a lack of awareness, and the accident was preventable. An aware driver should think, expect, and see hazardous situations in time to avoid collisions.
3. Was the driver under any physical stresses that could have been contributory? Did the accident happen near the end of a long day or long drive? Did overeating contribute to fatigue? Did the driver get prior sufficient sleep? Is the driver's vision faulty? Was the driver feeling ill?
4. Was the vehicle defective without the driver's knowledge? Was a pre-trip inspection done, and would it have discovered the defect? A car that pulls to the left or right when the driver applies the brakes, faulty windshield wipers, and similar items are excuses, and a driver using them is trying to evade responsibility. Sudden brake failure, loss of steering, or a blowout might be defects beyond the driver's ability to predict. However, pre-trip inspections and regularly scheduled maintenance should prevent most of these problems. If either of these are the cause of the accident, then the accident was probably preventable by the driver.
5. Could the driver have exercised better judgment by taking an alternate route through less congested areas to reduce the hazardous situations encountered?
6. Could the driver have done anything to avoid the accident?
7. Was the driver's speed safe for conditions?
8. Did the driver obey all traffic signals?
9. Was the driver's vehicle under control?

Intersection Collisions

Failure of our driver to yield the right-of-way, regardless of who has the right of way, as indicated by stop signs or lights, is preventable. The only exception to this is when the driver is properly proceeding through an intersection protected by lights or stop signs and the driver's vehicle is struck in the extreme rear side of the vehicle. Regardless of stop signs, stoplights, or right-of-way, a defensive driver recognizes that the right-of-way belongs to anyone who assumes it and should yield accordingly.

Questions to consider:

1. Did the driver approach the intersection at a speed safe for conditions?
2. Was the driver prepared to stop before entering the intersection?
3. At a blind corner, did the driver pull out slowly, ready to apply the brakes?
4. Did the driver look both ways before proceeding through the intersection?

Sideswipes

Sideswipes are often preventable. Defensive drivers do not get into a position where they can be forced into another vehicle or another vehicle can be forced into them. Defensive drivers continuously check for escape routes to avoid sideswipes. For two lane roads, this means a driver should pass another vehicle only when absolutely certain that he or she can safely complete the pass. A driver should also be ready to slow down and let a passing vehicle that has failed to judge safe passing distance back into the lane. A driver should make no sudden moves that may force another vehicle to swerve. If a driver sideswipes a stationary object while taking evasive action to avoid striking another car or a pedestrian, such an accident may not be preventable. However, you should consider what the driver could have done or failed to do immediately preceding the evasive action to be in the position of no other options.

A driver is also expected to anticipate the actions of an oncoming vehicle. Sideswiping an oncoming vehicle is often preventable. Again, evasive action, including leaving the roadway, may be necessary if an oncoming vehicle crosses into the driver's lane. Drivers are expected to allow merging vehicles to merge smoothly with them, and to merge smoothly on controlled access highways. Drivers are expected to be able to gauge distances properly when leaving a parking place and enter traffic smoothly.

Questions to consider:

1. Did the driver look to front and rear for approaching and overtaking traffic immediately before starting to pull away from the curb?
2. Did the driver signal before pulling away from the curb?
3. Did the driver look back rather than depend only upon rear-view mirrors?
4. Did the driver start into traffic only when this action would not require traffic to change its speed or direction in order to avoid his or her vehicle?

Head-on Collisions

A head-on collision with a vehicle traveling in the wrong lane may be preventable if the driver could have pulled off the road or taken other evasive action to prevent a collision. However, the driver should never drive into the other lane to avoid the oncoming vehicle. If the driver swerved off the road to avoid a head-on collision, the accident is non-preventable. The driver in this case made a good defensive driving decision, taking the lesser of two evils.

Many skidding conditions are caused by rain, freezing rain, fog, and snow, which all increase the hazard of travel. Oily road film, which builds up during a period of good weather, causes an especially treacherous condition during the first minutes of a rainfall. Loss of traction can be anticipated, and these accidents usually are preventable. Driving too fast for conditions is the most common reason why these types of accidents are preventable.

Questions to consider:

1. Was the driver operating at a safe speed considering weather and road conditions?
2. During inclement weather, was the driver keeping at least twice the safe following distance used for dry pavement?
3. Were all actions gradual?
4. Was the driver anticipating ice on bridges, in gutter, ruts, and near the curb?
5. Was the driver alert for water, ice or snow in shaded areas, loose gravel, sand, ruts, etc?

If a driver goes off the road or strikes another vehicle because of skidding, the accident is preventable.

Pedestrian Accidents

All types of pedestrian accidents, including collisions with pedestrians coming from between parked cars, are usually considered preventable. There are few instances where the action of pedestrians is so unreasonable that the operator could not be expected to anticipate such an occurrence.

Questions to consider:

1. Did the driver go through congested areas expecting that pedestrians would step in front of the vehicle?
2. Was the driver prepared to stop?
3. Did the driver keep as much clearance between his or her vehicle and parked vehicles, as safety permitted?
4. Did the driver stop when other vehicles had stopped to allow pedestrians to cross?
5. Did the driver wait for the green light or stop for the caution light?
6. Was the driver aware of children and prepared to stop if one ran into the street?
7. Did the driver give all pedestrians the right-of-way?
8. Did the driver stop for a school bus that was stopped and properly signaling that passengers were loading or unloading?

Backing Accidents

Backing a vehicle into another vehicle, an overhead obstruction, or a stationary object is normally preventable. The fact that someone was directing the driver in backing does not relieve the driver of the responsibility to back safely.

Questions to consider:

1. Was it necessary to back?
2. Did the driver plan ahead so that he or she could have pulled forward out of the parking space instead of backing?
3. Was it necessary to drive into the narrow street, dead-end alley, or driveway from which he or she backed?
4. If the driver could not see where he or she was backing: Did the driver try to get someone to guide him or her?
5. Did the driver look all around the vehicle before backing? Did the driver back immediately after looking?
6. Did the driver use the horn while backing? Were the back-up lights working?
7. Did the driver look to the rear without relying totally on the rear-view mirror?
8. If the distance was long, did the driver stop, get out, and look around occasionally?
9. Did the driver back slowly?
10. Did the driver judge clearances accurately?

Parking Accidents

Doors on our driver's parked vehicle that are damaged when opened on the traffic side are considered preventable accidents. The driver is responsible to see that the traffic side is clear of traffic, before any doors on that side are opened.

In most cases, if our driver, while driving, strikes a parked vehicle's opening door it is considered preventable. Usually our driver can see from a sufficient distance that the parked vehicle is occupied, and should therefore, be prepared to stop, should move closer to the center line or change lanes.

It is a driver's responsibility to park the vehicle so that it will remain stationary. A runaway type accident is preventable and blaming such a collision on defective parking brakes or other holding devices are inadequate excuses. A good pre-trip inspection and maintenance program will eliminate most opportunities for this type of accident being the result of mechanical failure.

Accidents occurring when vehicles are properly and legally parked are considered non preventable. Accidents occurring while the vehicle was double-parked or in a "No Parking" zone are preventable.

Questions to consider:

1. Was the vehicle parked on the proper side of the road?
2. Was it necessary to park there or was there a safer, only slightly less convenient place nearby?
3. Did the driver have to park on the traveled part of the highway, on the curve, or on the hill?
4. When required, did the driver warn traffic by emergency warning devices?
5. Did the driver park parallel to the curb?
6. Was it necessary to park so close to an alley or directly across from a driveway?

Collision with Obstructions

Obstructions can be avoided if the driver knows the height and width of the vehicle, pays attention to posted clearances, and takes the time to properly judge clearances.

Cargo Accidents

The accident should be considered preventable if the investigation shows a mechanical defect of which the driver was aware, a defect the driver should have found by inspecting the vehicle, or the driver caused the accident by rough and abusive handling. It is a driver's responsibility to secure cargo properly to prevent shifting, loss, or damage. Cargo should be safely stowed to prevent flying objects that can strike or distract the driver.

The company has the following requirements for fall protection at all of our worksites.

Fall Protection is Required

When working where there is a hazard of falling more than 6 feet from the perimeter of a structure, unprotected sides and edges, leading edges, through shaft ways and openings, sloped roof surfaces steeper than 7:12, or other sloped surfaces steeper than 40 degrees not otherwise adequately protected. Fall protection is also required when working in boom lifts.

Fall Protection Types

One of the following four types of fall protection systems will be used when our employees are exposed to fall hazards in excess of 6 feet:

1. Standard guardrails, cables or floor hole covers
2. Personal fall arrest system
3. Positioning devices
4. Fall restraint systems

Standard Guardrails, Safety Cables, or Covers

These are the easiest and most cost effective methods of providing fall protection and have a very high success rate. Standard guardrails, safety cables, floor hole and sky light covers are our preferred means of fall protection on job sites. The following rules will be followed when using them:

1. Railings shall be constructed of wood, or in an equally substantial manner from other materials, and shall consist of a top rail not less than 42 inches or more than 45 inches in height measured from the upper surface of the top rail to the floor, platform, runway or ramp level and a mid rail. The mid rail shall be halfway between the top rail and the floor, platform, runway or ramp. "Selected lumber" free from damage that affects its strength, shall be used.
2. Wooden posts shall be not less than 2 inches by 4 inches in cross section, spaced at 8-foot or closer intervals.
3. Wooden top railings shall be smooth and of 2-inch by 4-inch or larger material. Double, 1-inch by 4-inch members may be used for this purpose, provided that one member is fastened in a flat position on top of the posts and the other fastened in an edge-up position to the inside of the posts and the side of the top member. Mid rails shall be of at least 1-inch by 6-inch material.
4. The rails shall be placed on the side of the post that will afford the greatest support and protection.
5. All guardrails, including their connections and anchorage, shall be capable of withstanding a load of 13 pounds per linear foot applied either horizontally or vertically downward at the top rail.
6. Railings receiving heavy stresses from employees trucking or handling materials shall be provided additional strength by the use of heavier stock, closer spacing of posts, bracing, or by other means.
7. Floor, roof and skylight openings shall be guarded by a standard railing and toe boards or cover. Covering shall be capable

of safely supporting the greater of the weight of a 200-pound person or the weight of worker(s) and material(s) placed thereon.

8. Coverings shall be secured in place to prevent accidental removal or displacement, and shall bear a pressure sensitized, painted, or stenciled sign with legible letters not less than one inch high, stating: "Opening--Do Not Remove." Markings of chalk or keel shall not be used.
9. Ladder way floor openings or platforms shall be guarded by standard railings with standard toe boards on all exposed sides, except at the entrance to the opening, with the passage through the railing either provided with a swinging gate or so offset that a person cannot walk directly into the opening.
10. Floor holes, into which persons can accidentally walk, shall be guarded by either a standard railing with standard toe boards on all exposed sides, or a floor hole cover of standard strength and construction that is secured against accidental displacement. While the cover is not in place, the floor hole shall be protected by standard railings.
11. Wall openings, from which there is a drop of more than 4 feet, and the bottom of the opening is less than 3 feet above the working surface, shall be guarded with either a standard rail or intermediate rail or both.
12. An extension platform outside a wall opening onto which materials can be hoisted for handling shall have side rails or equivalent guards of standard specifications. One side of an extension platform may have removable railings in order to facilitate handling materials.
13. Wall opening protection barriers shall be of such construction and mounting that, when in place at the opening, the barrier is capable of withstanding a load of at least 200 pounds applied in any direction (except upward).
14. All elevator shafts in which cages are not installed and which are not enclosed with solid partitions and doors shall be guarded on all open sides by standard railings and toe boards.
15. A full body harness and lanyard are required when using boom lifts.

Personal Fall Arrest Systems

Personal fall arrest systems consist of a full body harness and a shock-absorbing lanyard attached to suitable anchorage. They are also an effective means of preventing fall accidents. The system does not actually stop you from falling, but catches you and safely stops you from hitting the level below. Fall arrest systems will be our preferred means of protection when standard guardrails, safety cables, or covers are not practical. The following rules, in addition to the manufacturer's requirements and OSHA regulations, will be observed:

1. Ropes and straps (webbing) used in lanyards, lifelines, and strength components of body harnesses shall be made from synthetic fibers except when they are used in conjunction with hot work where the lanyard may be exposed to damage from heat or flame.
2. Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and capable of supporting at least 5,000 pounds per employee attached, or shall be designed, installed, and used as part of a complete personal fall arrest system which maintains a safety factor of at least two; and under the supervision of a qualified person.
3. The attachment point of the body belt shall be located in the center of the wearer's back. The attachment point of the body harness shall be located in the center of the wearer's back near shoulder level, or above the wearer's head.
4. Where practical, the anchor end of the lanyard shall be secured at a level not lower than the employee's waist, limiting

the fall distance to a maximum of 4 feet.

5. Harnesses, lanyards, and other components shall be used only for employee protection as part of a personal fall arrest system and not to hoist materials.
6. Personal fall arrest systems and components subjected to impact loading shall be immediately removed from service and shall not be used again for employee protection until inspected and determined by a competent person to be undamaged and suitable for reuse.
7. The company shall provide for prompt rescue of employees in the event of a fall or shall assure that employees are able to rescue themselves.
8. Personal fall arrest systems shall be inspected prior to each use for wear, damage and other deterioration, and defective components shall be removed from service.
9. Any lanyard, safety harness, or drop line subjected to in-service loading, as distinguished from static load testing, shall be immediately removed from service and shall not be used again for employee safeguarding.
10. Personal fall arrest systems shall not be attached to guardrails, unless the guardrail is capable of safely supporting the load.
11. Each personal fall arrest system shall be inspected not less than twice annually by a competent person in accordance with the manufacturer's recommendations. The date of each inspection shall be documented.
12. Personal fall arrest systems will be rigged such that an employee can neither free fall more than 4 feet, nor contact any lower level.
13. Personal fall arrest systems will bring an employee to a complete stop. They will also limit maximum deceleration distance an employee travels to 3.5 feet and have sufficient strength to withstand twice the potential impact energy of an employee free falling a distance of 6 feet, or the free fall distance permitted by the system, whichever is less.

Positioning Device Systems

Positioning device systems are designed to allow employees to work with both hands free at elevated locations. By their very nature, they provide some level of fall protection. They are not as effective as railings or fall arrest systems. Positioning device systems may be used together with a fall arrest system for greater safety. Their use shall conform to the following provisions:

1. Positioning devices shall be rigged such that an employee cannot free fall more than 2 feet.
2. Positioning device systems shall be inspected prior to each use for wear, damage, and other deterioration, and defective components shall be removed from service.
3. Body belts, harnesses, and components shall be used only for employee protection (as part of a personal fall arrest system or positioning device system) and not to hoist materials.
4. The use of non-locking snap hooks is prohibited.
5. Anchorage points for positioning device systems shall be capable of supporting two times the intended load or 3,000 pounds, whichever is greater.

Personal Fall Restraint

Fall restraint systems are designed to prevent the wearer from reaching the edge or danger area and thus prevent them from falling. Body belts or harnesses may be used for personal fall restraint.

1. Body belts shall be at least one and five-eighths (1 5/8) inches wide.
2. Anchorage points used for fall restraint shall be capable of supporting 4 times the intended load.
3. Restraint protection shall be rigged to allow the movement of employees only as far as the sides of the working level or working area.

RESPIRATORY PROTECTION

Occasionally our work may necessitate the use of respirators to protect against air contaminants. Due to the limitations of respirators and their uncomfortable nature, the company will make every effort to provide other means of protection, such as local exhaust ventilation, or substitution of less hazardous material, prior to requiring employees to wear them.

When it is clearly impractical to remove harmful dusts, fumes, mists, vapors, or gases at their source, or where emergency protection against occasional and/or relatively brief exposure is needed, the company will provide, and the employee exposed to such hazard shall use, approved respiratory equipment.

Whenever respirators are required to be used to control harmful exposures, only respiratory equipment approved for that purpose shall be used and such equipment shall be approved by the National Institute for Occupational Safety and Health (NIOSH). Only parts approved for the specific respirator system shall be used for replacement.

General Respiratory Protection Guidelines:

1. Atmospheric contamination will be prevented wherever feasible through engineering controls such as enclosure or confinement of the operation, general and local exhaust ventilation, or substitution of less toxic materials. When effective engineering controls are not feasible, or while they are being instituted, appropriate respirators shall be used.
2. The company shall identify and evaluate the respiratory hazard(s) in the workplace; this evaluation shall include a reasonable estimate of employee exposures to respiratory hazard(s) and an identification of the contaminant's chemical state and physical form. Where we cannot identify or reasonably estimate the employee exposure, the atmosphere shall be considered to be immediately dangerous to life or health (IDLH).
3. Respirators shall be provided when such equipment is necessary to protect the health of the employee.
4. Only NIOSH-certified respirators shall be used. The respirator shall be used in compliance with the conditions of its certification.
5. The company will provide respirators that are applicable and suitable for the purpose intended. We shall select and provide an appropriate respirator based on the respiratory hazard(s) to which the worker is exposed and workplace and user factors that affect respirator performance and reliability.
6. Respirators shall be selected from a sufficient number of respirator models and sizes so that the respirator is acceptable to, and correctly fits, the user.
7. The safety program administrator is qualified by appropriate training or experience that is commensurate with the complexity of the program to administer or oversee the respiratory protection program and conduct the required evaluations of program effectiveness.
8. The company will provide respirators, training, and medical evaluations at no cost to the employee.
9. The company will provide a medical evaluation to determine the employee's ability to use a respirator, before the employee is fit tested or required to use the respirator in the workplace. We may discontinue an employee's medical evaluations when the employee is no longer required to use a respirator.
10. The company will ensure that employees using a tight-fitting facepiece respirator pass an appropriate qualitative fit test (QLFT) or quantitative fit test (QNFT).

11. The company will establish and implement procedures for the proper use of respirators. These requirements include prohibiting conditions that may result in facepiece seal leakage, preventing employees from removing respirators in hazardous environments, taking actions to ensure continued effective respirator operation throughout the work shift, and establishing procedures for the use of respirators in IDLH atmospheres.
12. We shall provide each respirator user with a respirator that is clean, sanitary, and in good working order. The Supervisor or Manager shall ensure that respirators are cleaned and disinfected.
13. All filters, cartridges and canisters used in the workplace must be legibly labeled and color-coded with the NIOSH approval label that must not be removed.
14. Training and information will be provided to employees who are required to use respirators. The training will be comprehensive, understandable, and recur annually, or more often if necessary.
15. The safety program administrator shall conduct evaluations of the workplace to ensure that the written respiratory protection program is being properly implemented, and to consult with employees to ensure that they are using the respirators properly.
16. Written information regarding medical evaluations, fit testing, and the respirator program shall be retained indefinitely. This information will facilitate employee involvement in the respirator program, assist us in auditing the adequacy of the program, and provide a record for compliance determinations by OSHA.
17. Where respirator use is not required by a particular standard or hazard, the company may provide respirators at the request of employees or permit employees to use their own respirators, if we determine that such respirator use will not in itself create a hazard. If voluntary respirator use is permissible, we shall provide the respirator users with the information contained in Appendix D of section 5144 8CCR. ("Information for Employees Using Respirators When Not Required Under the Standard.")

Respirator Selection Requirements

The proper respirator for the job and hazard shall be selected. This selection will be made in accordance with ANSI Z88.2-1980 standards. The correct respirator shall be specified for each job. The individual issuing them shall be adequately instructed to insure that the correct respirator is used.

The manufacturers' recommendations and literature will also be reviewed to determine if the respirator provides protection against the expected contaminants. For instance, dust masks do not provide protection against gasses or vapors.

The safety program administrator or another qualified individual shall review and approve all breathing air compressors and installations for compliance with appropriate OSHA regulations and safety procedures prior to use.

Respirators for IDLH atmospheres.

We shall provide the following respirators for employee use in IDLH atmospheres:

- A full face piece pressure demand SCBA certified by NIOSH for a minimum service life of thirty minutes, or
- A combination full face piece pressure demand supplied-air respirator (SAR) with auxiliary self-contained air supply.
- Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

- All oxygen-deficient atmospheres shall be considered IDLH.

Respirators for atmospheres that are not IDLH.

The company shall provide a respirator that is adequate to protect the health of the employee and ensure compliance with all other OSHA statutory and regulatory requirements, under routine and reasonably foreseeable emergency situations. The respirator selected shall be appropriate for the chemical state and physical form of the contaminant.

For protection against gases and vapors:

- An atmosphere-supplying respirator, or
- An air-purifying respirator, provided that the respirator is equipped with an end-of-service-life indicator (ESLI) certified by NIOSH for the contaminant; or if there is no ESLI appropriate for conditions in the workplace, we will implement a change schedule for canisters and cartridges that is based on objective information or data that will ensure that canisters and cartridges are changed before the end of their service life.

For protection against particulates:

- An atmosphere-supplying respirator; or
- An air-purifying respirator equipped with a filter certified by NIOSH under 30 CFR part 11 as a high efficiency particulate air (HEPA) filter, or an air-purifying respirator equipped with a filter certified for particulates by NIOSH under 42 CFR part 84; or
- For contaminants consisting primarily of particles with mass median aerodynamic diameters (MMAD) of at least 2 micrometers, an air-purifying respirator equipped with any filter certified for particulates by NIOSH.

Medical Evaluation Procedures

1. Employees shall not be assigned to tasks requiring the use of respirators unless it has been determined that they are physically able to perform the work while using the required respiratory equipment.
2. The company shall identify a physician or other licensed health care professional (PLHCP) to perform medical evaluations.
3. The medical evaluation shall include any medical tests, consultations, or diagnostic procedures that the PLHCP deems necessary to make a final determination.
4. Medical questionnaires and examinations shall be administered confidentially during the employee's normal working hours or at a time and place convenient to the employee.
5. The employee shall have an opportunity to discuss the examination results with the PLHCP.
6. The following information must be provided to the PLHCP before the PLHCP makes a recommendation concerning an employee's ability to use a respirator:
 - The type and weight of the respirator to be used by the employee;
 - The duration and frequency of respirator use (including use for rescue and escape);
 - The expected physical work effort;
 - Additional protective clothing and equipment to be worn; and
 - Temperature and humidity extremes that may be encountered.

7. The company shall provide the PLHCP with a copy of this written respiratory protection program and a copy of the OSHA regulations if they do not already have them.
8. In determining the employee's ability to use a respirator, the company shall obtain a written recommendation regarding the employee's ability to use the respirator from the PLHCP. The recommendation shall provide only the following information:
 - Any limitations on respirator use related to the medical condition of the employee, or relating to the workplace conditions in which the respirator will be used, including whether or not the employee is medically able to use the respirator;
 - The need, if any, for follow-up medical evaluations; and
 - A statement that the PLHCP has provided the employee with a copy of the PLHCP's written recommendation.
9. If the respirator is a negative pressure respirator and the PLHCP finds a medical condition that may place the employee's health at increased risk if the respirator is used, the company shall provide a powered air purifying respirator (PAPR) if the PLHCP's medical evaluation finds that the employee can use such a respirator; if a subsequent medical evaluation finds that the employee is medically able to use a negative pressure respirator, then we are no longer required to provide a PAPR.
10. The company shall provide additional medical evaluations that comply with the requirements of this section if:
 - An employee reports medical signs or symptoms that are related to ability to use a respirator;
 - A PLHCP, supervisor, or the respirator program administrator informs the employer that an employee needs to be reevaluated;
 - Information from the respiratory protection program, including observations made during fit testing and program evaluation, indicates a need for employee reevaluation; or
 - A change occurs in workplace conditions (e.g., physical work effort, protective clothing, temperature) that may result in a substantial increase in the physiological burden placed on an employee.

Fit Testing

1. The company shall ensure that an employee using a tight-fitting face piece respirator is fit tested prior to initial use of the respirator, whenever a different respirator face piece (size, style, model or make) is used, and at least annually thereafter.
2. We shall conduct an additional fit test whenever the employee reports, or the employer, PLHCP, supervisor, or program administrator makes visual observations of, changes in the employee's physical condition that could affect respirator fit. Such conditions include, but are not limited to, facial scarring, dental changes, cosmetic surgery, or an obvious change in body weight.
3. If after passing a QLFT or QNFT, the employee subsequently notifies the program administrator, supervisor, or PLHCP that the fit of the respirator is unacceptable, the employee shall be given a reasonable opportunity to select a different respirator face piece and to be retested.
4. The fit test shall be administered using an OSHA-accepted QLFT or QNFT protocol.

Usage Rules

1. The company shall not permit respirators with tight-fitting face pieces to be worn by employees who have:
 - Facial hair that comes between the sealing surface of the face piece and the face or that interferes with valve function; or
 - Any condition that interferes with the face-to-face piece seal or valve function.
2. If an employee wears corrective glasses or goggles or other personal protective equipment, we shall ensure that such equipment is worn in a manner that does not interfere with the seal of the face piece to the face of the user.
3. For all tight-fitting respirators, we shall ensure that employees perform a user seal check each time they put on the respirator.
4. Appropriate surveillance shall be maintained of work area conditions and degree of employee exposure or stress. When there is a change in work area conditions or degree of employee exposure or stress that may affect respirator effectiveness, we shall reevaluate the continued effectiveness of the respirator.
5. Respiratory equipment shall not be passed on from one person to another until it has been cleaned and sanitized. Respirators individually assigned should be marked to indicate to whom it was assigned. This mark shall not affect the respirator performance in any way. The date of issuance should be recorded.
6. When not in use, respirators shall be stored to protect against dust, sunlight, extreme temperatures, excessive moisture, or damaging chemicals. Plastic zip lock bags are suitable for storage.
7. The company shall ensure that employees leave the respirator use area:
 - To wash their faces and respirator facepieces as necessary to prevent eye or skin irritation associated with respirator use; or
 - If they detect vapor or gas breakthrough, changes in breathing resistance, or leakage of the facepiece; or
 - To replace the respirator or the filter, cartridge, or canister elements.
8. If the employee detects vapor or gas breakthrough, changes in breathing resistance, or leakage of the facepiece, we will replace or repair the respirator before allowing the employee to return to the work area.
9. For all IDLH atmospheres, the company shall ensure that:
 - One employee or, when needed, more than one employee is located outside the IDLH atmosphere;
 - Visual, voice, or signal line communication is maintained between the employee(s) in the IDLH atmosphere and the employee(s) located outside the IDLH atmosphere;
 - The employee(s) located outside the IDLH atmosphere are trained and equipped to provide effective emergency rescue;
 - The Supervisor or designee is notified before the employee(s) located outside the IDLH atmosphere enter the IDLH atmosphere to provide emergency rescue;
 - The Supervisor or designee authorized to do so by «Company_Name», once notified, provides necessary assistance appropriate to the situation;
 - Employee(s) located outside the IDLH atmospheres are equipped with pressure demand or other positive pressure SCBAs, or a pressure demand or other positive pressure supplied-air respirator with auxiliary SCBA; and either appropriate retrieval equipment for removing the employee(s) who enter(s) these hazardous atmospheres where retrieval equipment would contribute to the rescue of the employee(s) and would not increase the overall risk

resulting from entry; or equivalent means for rescue where retrieval equipment is not required.

Maintenance, Inspection and Care of Respirators.

1. The company shall ensure that respirators are cleaned and disinfected using procedures recommended by the respirator manufacturer, provided that such procedures are of equivalent effectiveness to OSHA regulations. The respirators shall be cleaned and disinfected at the following intervals:
 - Respirators issued for the exclusive use of an employee shall be cleaned and disinfected as often as necessary to be maintained in a sanitary condition;
 - Respirators issued to more than one employee shall be cleaned and disinfected before being worn by different individuals;
 - Respirators maintained for emergency use shall be cleaned and disinfected after each use; and
 - Respirators used in fit testing and training shall be cleaned and disinfected after each use.
2. All respirators shall be stored to protect them from damage, contamination, dust, sunlight, extreme temperatures, excessive moisture, and damaging chemicals, and they shall be packed or stored to prevent deformation of the facepiece and exhalation valve.
3. Emergency respirators shall be:
 - Kept accessible to the work area;
 - Stored in compartments or in covers that are clearly marked as containing emergency respirators; and
 - Stored in accordance with any applicable manufacturer instructions.
4. All respirators used in routine situations shall be inspected before each use and during cleaning;
5. All respirators maintained for use in emergency situations shall be inspected at least monthly and in accordance with the manufacturer's recommendations, and shall be checked for proper function before and after each use; and
6. Emergency escape-only respirators shall be inspected before being carried into the workplace for use.
7. The company shall ensure that respirator inspections include the following:
 - A check of respirator function, tightness of connections, and the condition of the various parts including, but not limited to, the facepiece, head straps, valves, connecting tube, and cartridges, canisters or filters; and
 - A check of elastomeric parts for pliability and signs of deterioration.
8. In addition to the requirements above, self-contained breathing apparatus shall be inspected monthly.
9. Air and oxygen cylinders shall be maintained in a fully charged state and shall be recharged when the pressure falls to 90% of the manufacturer's recommended pressure level. The employer shall determine that the regulator and warning devices function properly.
10. For respirators maintained for emergency use, the company shall:
 - Certify the respirator by documenting the date the inspection was performed, the name (or signature) of the person who made the inspection, the findings, required remedial action, and a serial number or other means of identifying the inspected respirator; and

- Provide this information on a tag or label that is attached to the storage compartment for the respirator, is kept with the respirator, or is included in inspection reports stored as paper or electronic files. This information shall be maintained until replaced following a subsequent certification.
11. Repairs. The company shall ensure that respirators that fail an inspection or are otherwise found to be defective are removed from service, and are discarded or repaired or adjusted in accordance with the following procedures:
- Repairs or adjustments to respirators are to be made only by persons appropriately trained to perform such operations and shall use only the respirator manufacturer's NIOSH-approved parts designed for the respirator;
 - Repairs shall be made according to the manufacturer's recommendations and specifications for the type and extent of repairs to be performed; and
 - Reducing and admission valves, regulators, and alarms shall be adjusted or repaired only by the manufacturer or a technician trained by the manufacturer.

Training

1. The company shall ensure that each employee required to use a respirator can demonstrate knowledge of at least the following:
 - Why the respirator is necessary and how improper fit, usage, or maintenance can compromise the protective effect of the respirator;
 - What the limitations and capabilities of the respirator are;
 - How to use the respirator effectively in emergency situations, including situations in which the respirator malfunctions;
 - How to inspect, put on and remove, use, and check the seals of the respirator;
 - What the procedures are for maintenance and storage of the respirator;
 - How to recognize medical signs and symptoms that may limit or prevent the effective use of respirators; and
2. The training shall be conducted in a manner that is understandable to the employee.
3. The training shall be provided prior to requiring the employee to use a respirator in the workplace.
4. Retraining shall be administered annually, and when the following situations occur:
 - Changes in the workplace or the type of respirator render previous training obsolete;
 - Inadequacies in the employee's knowledge or use of the respirator indicate that the employee has not retained the requisite understanding or skill; or
 - Any other situation arises in which retraining appears necessary to ensure safe respirator use.

Program Evaluation

1. The safety program administrator shall conduct evaluations of the workplace as necessary to ensure that the provisions of the current written program are being effectively implemented and that it continues to be effective.
2. The safety program administrator shall regularly consult employees required to use respirators to assess the employees' views on program effectiveness and to identify any problems. Any problems that are identified during this assessment shall be corrected. Factors to be assessed include, but are not limited to:

- Respirator fit (including the ability to use the respirator without interfering with effective workplace performance);
- Appropriate respirator selection for the hazards to which the employee is exposed;
- Proper respirator use under the workplace conditions the employee encounters; and
- Proper respirator maintenance.

Recordkeeping

1. Records of medical evaluations must be retained and made available to regulatory agencies.
2. The company shall establish a record of the qualitative and quantitative fit tests administered to an employee including:
 - The name or identification of the employee tested;
 - Type of fit test performed;
 - Specific make, model, style, and size of respirator tested;
 - Date of test; and
 - The pass/fail results for QLFTs or the fit factor and strip chart recording or other recording of the test results for QNFTs.
 - Fit test records shall be retained for respirator users until the next fit test is administered.
3. Program records shall be made available upon request to affected employees and to governing or regulatory agencies for examination and copying.

Procedures for Cleaning Respirators.

1. Remove filters, cartridges, or canisters. Disassemble facepieces by removing speaking.
2. Wash components in warm (43 deg. C [110 deg. F] maximum) water with a mild detergent or with a cleaner recommended by the manufacturer. A stiff bristle (not wire) brush may be used to facilitate the removal of dirt.
3. Rinse components thoroughly in clean, warm (43 deg. C [110 deg. F] maximum), preferably running water. Drain.
4. When the cleaner used does not contain a disinfecting agent, respirator components should be immersed for two minutes in one of the following:
 - Hypochlorite solution (50 ppm of chlorine) made by adding approximately one milliliter of laundry bleach to one liter of water at 43 deg. C (110 deg. F); or,
 - Aqueous solution of iodine (50 ppm iodine) made by adding approximately 0.8 milliliters of tincture of iodine (6-8 grams ammonium and/or potassium iodide/100 cc of 45% alcohol) to one liter of water at 43 deg. C (110 deg. F); or,
 - Other commercially available cleansers of equivalent disinfectant quality when used as directed, if their use is

recommended or approved by the respirator manufacturer.

5. Rinse components thoroughly in clean, warm (43 deg. C [110 deg. F] maximum), preferably running water. Drain. The importance of thorough rinsing cannot be overemphasized. Detergents or disinfectants that dry on facepieces may result in dermatitis. In addition, some disinfectants may cause deterioration of rubber or corrosion of metal parts if not completely removed.
6. Components should be hand-dried with a clean lint-free cloth or air-dried.
7. Reassemble facepiece, replacing filters, cartridges, and canisters where necessary.
8. Test the respirator to ensure that all components work properly.

Mandatory Information for Employees Using Respirators When Not Required

Respirators are an effective method of protection against designated hazards when properly selected and worn. Respirator use is encouraged, even when exposures are below the exposure limit, to provide an additional level of comfort and protection for workers. However, if a respirator is used improperly or not kept clean, the respirator itself can become a hazard to the worker. Sometimes, workers may wear respirators to avoid exposures to hazards, even if the amount of hazardous substance does not exceed the limits set by OSHA standards. If your employer provides respirators for your voluntary use, or if you provide your own respirator, you need to take certain precautions to be sure that the respirator itself does not present a hazard.

You should do the following:

1. Read and heed all instructions provided by the manufacturer on use, maintenance, cleaning and care, and warnings regarding the respirators limitations.
2. Choose respirators certified for use to protect against the contaminant of concern. NIOSH, the National Institute for Occupational Safety and Health of the U.S. Department of Health and Human Services, certifies respirators. A label or statement of certification should appear on the respirator or respirator packaging. It will tell you what the respirator is designed for and how much it will protect you.

3. Do not wear your respirator into atmospheres containing contaminants for which your respirator is not designed to protect against. For example, a respirator designed to filter dust particles will not protect you against gases, vapors, or very small solid particles of fumes or smoke.
4. Keep track of your respirator so that you do not mistakenly use someone else's respirator.

The company has developed the following procedures to protect our employees and reduce the risk of accidents. We will also conduct a periodic review of electrical safety, energy control procedures, and lock-out / tag-out, at least annually, to ensure that the procedure and the requirements of this section are being followed.

This procedure is binding upon all employees. All employees will be instructed in the significance of electrical safety, energy control procedures, and lock-out / tag-out. Each new employee shall be instructed by their Supervisor in the purpose and use of these procedures.

All Equipment and Installations

1. Only trained, qualified, and authorized employees will be allowed to make electrical repairs or work on electrical equipment or installations.
2. All electrical equipment and systems shall be treated as energized until tested or otherwise proven to be de-energized.
3. All energized equipment and installations will be de-energized prior to the commencement of any work. If the equipment or installation must be energized for test or other purposes, special precautions will be taken to protect against the hazards of electric shock.
4. All equipment shall be locked out to protect against accidental or inadvertent operation when such operation could cause injury to personnel. Do not attempt to operate any switch, valve, or other energy-isolating device bearing a lock.
5. Safety grounds shall always be used where there is a danger of shock from back feeding or other hazards.
6. Polyester clothing or other flammable types of clothing shall not be worn near electrical circuits. Cotton clothing is much less likely to ignite from arc blast. Employees working on live circuits shall be provided Nomex or equivalent fire resistant clothing.
7. Suitable eye protection must be worn at all times while working on electrical equipment.
8. Always exercise caution when energizing electrical equipment or installations. Take steps to protect employees from arc blast and exploding equipment in the event of a fault.
9. All power tools will be grounded or double insulated. Tools with defective cords or wiring shall not be used.
10. Suitable temporary barriers or barricades shall be installed when access to open enclosures containing exposed energized equipment is not under the control of an authorized person.

Energized Equipment or Systems

Work shall not be performed on exposed energized parts of equipment or systems until the following conditions are met:

1. Responsible supervision has determined that the work is to be performed while the equipment or systems are energized.
2. Involved personnel have received instructions on the work techniques and hazards involved in working on energized equipment and appropriate equipment to perform the job has been provided.

3. Suitable personal protective equipment has been provided and is used. Suitable insulated gloves shall be worn for voltages in excess of 300 volts, nominal.
4. Suitable eye protection, including face shield and safety glasses or goggles, has been provided and is used.
5. Fire resistant clothing such as Nomex suits is worn.
6. Where required, suitable barriers, barricades, tags, or signs are in place for personnel protection.

After the required work on an energized system or equipment has been completed, an authorized person shall be responsible for:

1. Removing from the work area any personnel and protective equipment.
2. Reinstalling all permanent barriers or covers.

De-energized Equipment or Systems

A qualified person shall be responsible for completing the following before working on de-energized electrical equipment or systems, unless the equipment is physically removed from the wiring system:

1. Notifying all involved personnel.
2. Locking the disconnecting means in the "open" position with the use of lockable devices, such as padlocks, combination locks or disconnecting of the conductor(s) or other positive methods or procedures which will effectively prevent unexpected or inadvertent energizing of a designated circuit, equipment or appliance.
3. Tagging the disconnecting means with suitable accident prevention tags.
4. Effectively blocking the operation or dissipating the energy of all stored energy devices which present a hazard, such as capacitors or pneumatic, spring-loaded and like mechanisms. This may require the installation of safety grounds.
5. Testing the equipment to ensure it is de-energized.

Energizing (or Re-energizing) Equipment or Systems

A qualified and authorized person shall be responsible for completing the following before energizing equipment or systems that have been de-energized:

1. Determining that all persons are clear from hazards which might result from the equipment or systems being energized including arc blast or explosions caused by unexpected faults.
2. Removing locking devices and tags. Only the employee who placed them may remove locking devices and tags. Locking devices and tags shall be removed upon completion of the work and after the installation of the protective guards and/or safety interlock systems.

Suitable accident prevention tags shall be used to control a specific hazard. Such tags shall provide the following minimum information:

1. Reason for placing tag.
2. Name of person placing the tag and how that person may be contacted.
3. Date tag was placed.

Lock-out / Tag-out

Machinery or equipment capable of movement shall be stopped and the power source de-energized or disengaged, and locked out. If necessary, the moveable parts shall be mechanically blocked or secured to prevent inadvertent movement during cleaning, servicing or adjusting operations unless the machinery or equipment must be capable of movement during this period in order to perform the specific task. If so, the hazard of movement shall be minimized.

Equipment or power driven machines equipped with lockable controls, or readily adaptable to lockable controls, shall be locked out or positively sealed in the "off" position during repair work and setting-up operations. In all cases, accident prevention signs and/or tags shall be placed on the controls of the equipment or machines during repair work.

The company will provide a sufficient number of accident prevention signs or tags and padlocks, seals or other similarly effective means that may be required by any reasonably foreseeable repair.

Sequence of Lockout Procedure

1. Notify all affected employees that a lockout is required and the reason therefore.
2. If the equipment is operating, shut it down by the normal stopping procedure (such as: depress stop button, open toggle switch).
3. Operate the switch, valve, or other energy isolating devices so that the energy source(s) (electrical, mechanical, hydraulic, other) is disconnected or isolated from the equipment.
4. Stored energy, such as that in capacitors, springs, elevated machine members, rotating fly wheels, hydraulic systems, and air, gas, steam or water pressure, must also be dissipated or restrained by methods such as grounding, repositioning, blocking, bleeding down.
5. Lockout energy isolating devices with an assigned individual lock.
6. After ensuring that no personnel are exposed and as a check on having disconnected the energy sources, operate the push button or other normal operating controls to make certain the equipment will not operate. CAUTION: Return operating controls to neutral position after the test.

Procedure Involving More Than One Person

If more than one individual is required to lock out equipment, each shall place his/her own personal lock on the energy isolating device(s). One designated individual of a work crew or a Supervisor, with the knowledge of the crew, may lock out equipment for the whole crew. In such cases, it may be the responsibility of the individual to carry out all steps of the lockout procedure and inform the crew when it is safe to work on the equipment. Additionally, the designated individual shall not remove a crew lock until it has been verified that all individuals are clear.

Testing Equipment during Lockout

In many maintenance and repair operations, machinery may need to be tested, and for that purpose energized, before additional maintenance work can be performed. This procedure must be followed:

1. Clear all personnel to safety.
2. Clear away tools and materials from equipment.
3. Remove lockout devices and re-energize systems, following the established safe procedure.
4. Proceed with tryout or test.
5. Neutralize all energy sources once again, purge all systems, and lockout prior to continuing work.

Equipment design and performance limitations may dictate that effective alternative worker protection be provided when the established lock-out procedure is not feasible.

Restoring Equipment to Service

After the work is completed and the equipment is ready to be returned to normal operation, this procedure must be followed:

1. Remove all non-essential items.
2. See that all equipment components are operationally intact, including guards and safety devices. Repair or replace defective guards before removing lockouts.
3. Remove each lockout device using the correct removal sequence.
4. Make a visual check before restoring energy to ensure that everyone is physically clear of the equipment.

CONFINED SPACE OPERATIONS

Occasionally in our work, we may encounter confined spaces. Confined space work requires special safety precautions to ensure that employees are not overcome by dangerous air contaminants or oxygen deficiency. In some cases, there may be fire or explosion hazards in confined spaces that do not exist in open areas. Many workers have been killed or seriously injured in confined spaces. To avoid this, employees must adhere to the following rules. This section prescribes minimum standards for preventing employee exposure to dangerous air contamination and/or oxygen deficiency in confined spaces. In some cases, extra precautions may be necessary. As always, if you are unsure, ask for assistance.

Definitions

A confined space has the following properties:

1. Existing ventilation is insufficient to remove dangerous air contamination and/or oxygen deficiency that may exist or develop.
2. Ready access or egress for the removal of a suddenly disabled employee is difficult due to the location and/or size of the opening(s).
3. The area is not designed for continuous human occupancy.

Dangerous air contamination means an atmosphere presenting a threat of causing death, injury, acute illness, or disablement due to the presence of flammable and/or explosive, toxic, or otherwise injurious or incapacitating substances.

Dangerous air contamination due to the flammability of a gas or vapor is defined as an atmosphere containing the gas or vapor at a concentration greater than 20 percent of its lower explosive (lower flammable) limit.

Dangerous air contamination due to a combustible particulate is defined as a concentration greater than 20 percent of the minimum explosive concentration of the particulate.

Dangerous air contamination due to the toxicity of a substance is defined as the atmospheric concentration immediately hazardous to life or health. This definition of dangerous air contamination due to the toxicity of a substance does not preclude the requirement to control harmful exposures to toxic substances at concentrations less than those immediately hazardous to life or health.

Oxygen deficiency. An atmosphere containing oxygen at a concentration of less than 19.5 percent by volume.

Oxygen rich. An atmosphere containing oxygen at a concentration of more than 22 percent by volume. This creates additional fire hazards.

Typical Confined Spaces:

- Vaults
- Pits
- Tubs
- Vats
- Ducts
- Boilers

- Silos
- Sewers
- Compartments

Prior to Confined Space Entry:

1. Written, understandable operating and rescue procedures shall be developed and shall be provided to affected employees. The operating procedures shall include provision for the surveillance of the surrounding area to avoid hazards such as drifting vapors from tanks, piping and sewers.
2. All employees, including standby persons if needed, will be trained in the operating and rescue procedures, including instructions as to the hazards they may encounter.
3. Any lines, pipes or hoses which may convey flammable, injurious, or incapacitating substances into the space shall be disconnected, blinded, or blocked off by other positive means to prevent the development of dangerous air contamination and/or oxygen deficiency within the space. The disconnection or blind shall be so located or done in such a manner that inadvertent reconnection of the line or removal of the blind is effectively prevented.
4. The space shall be emptied, flushed, or otherwise purged of flammable, injurious or incapacitating substances to the extent feasible.
5. The air shall be tested with an appropriate device or method to determine whether dangerous air contamination and/or an oxygen deficiency exists and a written record of such testing results shall be made and kept at the work site for the duration of the work. Affected employees and/or their representative shall be afforded an opportunity to review and record the testing results.
6. Where interconnected spaces are blinded off as a unit, each space shall be tested and the results recorded. The most hazardous condition found shall govern the entry procedures to be followed.

Confined Space Entry if Tests Show No Hazard

If dangerous air contamination and/or oxygen deficiency does not exist within the space, as demonstrated by tests performed in accordance with the pre-entry procedures, entry into and work within the space may proceed subject to the following provisions:

1. Air testing, in accordance with the pre-entry procedures, shall be conducted with sufficient frequency to ensure that the development of dangerous air contamination and/or oxygen deficiency does not occur during the performance of any operation.
2. Work stops, employees exit, and additional precautions are taken if dangerous air contamination and/or oxygen deficiency does develop.

Confined Space Entry if Tests Show Hazards are Present or are Likely to Develop

Where the existence of dangerous air contamination and/or oxygen deficiency is demonstrated by tests performed in accordance with the pre-entry procedures or if the development of dangerous air contamination and/or an oxygen deficiency

is imminent, the following requirements shall also apply:

1. Existing ventilation shall be augmented by appropriate means.
2. When additional ventilation has removed dangerous air contamination and/or oxygen deficiency as demonstrated by additional testing conducted (and recorded), entry into and work within the space may proceed.
3. No source of ignition shall be introduced until the implementation of appropriate provisions of this section have ensured that dangerous air contamination due to flammable and/or explosive substances does not exist.
4. Whenever oxygen-consuming equipment such as welding torches, furnaces and the like are to be used, measures shall be taken to ensure adequate combustion air and exhaust gas venting.
5. To the extent feasible, provision shall be made to permit ready entry and exit.
6. Where it is not feasible to provide for ready exit from spaces equipped with automatic fire suppression systems employing harmful design concentrations of toxic or oxygen-displacing gases, or total foam flooding, such systems shall be deactivated. Where it is not practical or safe to deactivate such systems, the use of respiratory protective equipment, such as SCBA, shall apply during entry into and work within such spaces.

Confined Spaces Where Dangerous Air Contamination Cannot be Removed by Ventilation

It is the policy of the company to only work in a confined space if it can be made safe by the means listed above. We will not work in confined spaces where there is an ongoing hazard of air contamination or oxygen deficiency. These operations require extra measures and precautions beyond our immediate ability to perform. If such work does become necessary, a separate program will be developed.

Each year about 100 workers are killed and almost 95,000 injured in industrial truck accidents across the country. To properly protect our employees from such accidents, the company has adopted the following Forklift Safety Program.

General

The company will ensure that each powered industrial truck operator is competent to operate a powered industrial truck safely, as demonstrated by the successful completion of the training and evaluation specified below.

Prior to permitting an employee to operate a powered industrial truck (except for training purposes), the company shall ensure that the employee has successfully completed a training program.

Training Program Implementation.

Trainees may operate a powered industrial truck only:

- under the direct supervision of persons who have the knowledge, training, and experience to train operators and evaluate their competence; and
- where such operation does not endanger the trainee or other employees.

Training shall consist of a combination of formal instruction (e.g., lecture, discussion, interactive computer learning, video tape, written material), practical training (demonstrations performed by the trainer and practical exercises performed by the trainee), and evaluation of the operator's performance in the workplace.

All operator training and evaluation shall be conducted by persons who have the knowledge, training, and experience to train powered industrial truck operators and evaluate their competence.

Note: This section does not require that the training be given by any particular individual or organization. The trainer must only be able to demonstrate that they have appropriate knowledge, training and experience to train others and evaluate their competence.

Training Program Content.

Powered industrial truck operators shall receive initial training in the following topics.

- Operating instructions, warnings, and precautions for the types of truck the operator will be authorized to operate;
- Differences between the truck and the automobile;
- Truck controls and instrumentation: where they are located, what they do, and how they work;
- Engine or motor operation;
- Steering and maneuvering;
- Visibility (including restrictions due to loading);
- Fork and attachment adaptation, operation, and use limitations;

- Vehicle capacity;
- Vehicle stability;
- Any vehicle inspection and maintenance that the operator will be required to perform;
- Refueling and/or charging and recharging of batteries;
- Operating limitations;
- Any other operating instructions, warnings, or precautions listed in the operator's manual for the types of vehicle that the employee is being trained to operate.
- Workplace-related topics:
- Surface conditions where the vehicle will be operated;
- Composition of loads to be carried and load stability;
- Load manipulation, stacking, and unstacking;
- Pedestrian traffic in areas where the vehicle will be operated;
- Narrow aisles and other restricted places where the vehicle will be operated;
- Hazardous locations where the vehicle will be operated;
- Ramps and other sloped surfaces that could affect the vehicle's stability;
- Closed environments and other areas where insufficient ventilation or poor vehicle maintenance could cause a buildup of carbon monoxide or diesel exhaust;
- Other unique or potentially hazardous environmental conditions in the workplace that could affect safe operation;
- The requirements of this section.

Refresher Training and Evaluation.

Refresher training, including an evaluation of the effectiveness of that training, shall be conducted to ensure that the operator has the knowledge and skills needed to operate the powered industrial truck safely.

Refresher training in relevant topics shall be provided to the operator when:

- The operator has been observed to operate the vehicle in an unsafe manner;
- The operator has been involved in an accident or near-miss incident;
- The operator has received an evaluation that reveals that the operator is not operating the truck safely;
- The operator is assigned to drive a different type of truck; or
- A condition in the workplace changes in a manner that could affect safe operation of the truck.

An evaluation of each powered industrial truck operator's performance shall be conducted at least once every three years.

Avoidance of Duplicative Training.

If an operator has previously received training in a topic specified above, and such training is appropriate to the truck and working conditions encountered, additional training in that topic is not required if the operator has been evaluated and found competent to operate the truck safely.

Note: This section reduces the training requirement for previously trained operators provided we can demonstrate that the operator knows the material. Since some of the required training is unique to the area where the lift will be operated, we must still cover these areas even if the employee was previously trained.

Certification.

The company shall certify that each operator has been trained and evaluated as required by this paragraph (I). The certification shall include the name of the operator, the date of the training, the date of the evaluation, and the identity of the person(s) performing the training or evaluation.

The program administrator will ensure the maintenance of all Safety Program records, for the listed periods, including:

- | | |
|--|----------------------|
| 1. New Employee Safety Orientation forms | length of employment |
| 2. Code of Safe Practices Receipt | length of employment |
| 3. Disciplinary actions for safety | 1 year |
| 4. Safety inspections | 2 years |
| 5. Safety meeting reports | 2 years |
| 6. Safety Contact Reports | 2 years |
| 7. Accident investigations | 5 years |
| 8. Federal or State OSHA log of injuries | 5 years |
| 9. Inventory of Hazardous Materials (if any) | forever |
| 10. Employee exposure or medical records | forever |

Records are available for review at the main office.

APPENDIXES

1. HAZARD ASSESSMENT AND CORRECTION RECORD

2. ACCIDENT / EXPOSURE INVESTIGATION FORM

3. WORKER TRAINING AND INSTRUCTION RECORD

4. EMPLOYEE SAFETY CONTACT REPORT

5. NEW EMPLOYEE SAFETY ORIENTATION

6. CODE OF SAFE WORK PRACTICES RECEIPT

7. SAFETY COMMITTEE MEETING MINUTES

8. SAFETY MEETING MINUTES

9. FACILITY INSPECTION CHECKLISTS

HAZARD ASSESSMENT AND CORRECTION RECORD

Date of Inspection: _____ Person Conducting Inspection: _____

Unsafe Condition or Work Practice:

Corrective Action Taken:

Date of Inspection: _____ Person Conducting Inspection: _____

Unsafe Condition or Work Practice:

Corrective Action Taken:

Date of Inspection: _____ Person Conducting Inspection: _____

Unsafe Condition or Work Practice:

Corrective Action Taken:

ACCIDENT / EXPOSURE INVESTIGATION REPORT

Date & Time of Accident:

Location:

Accident Description:

Workers Involved:

Preventive Action Recommendations:

Corrective Actions Taken:

WORKER TRAINING AND INSTRUCTION RECORD

[illegible]

EMPLOYEE SAFETY CONTACT REPORT

Work site: _____
Manager / Supervisor: _____
Employee name _____
Date _____
Job title _____

Safety concern:

Corrective action:

Signed: _____
Employee

Signed: _____
Manager / Supervisor

NEW EMPLOYEE SAFETY ORIENTATION

The Supervisor will verbally cover the following items with each new employee on the first day of their employment.

Employee Name: _____

Start Date: _____

Job Title / Position: _____

Instruction has been received in the following areas.

- ☐ 1. Code of Safe Practices.*
- ☐ 2. Hazard Communication (chemicals) Employee Training Handbook.*
- ☐ 3. Driving Safety Rules.*
- ☐ 4. Safety rule enforcement procedures.
- ☐ 5. Necessity of reporting ALL injuries, no matter how minor, IMMEDIATELY.
- ☐ 6. Proper method of reporting safety hazards.
- ☐ 7. Emergency procedures and First Aid.
- ☐ 8. Proper work clothing & required personal protective equipment.
- ☐ 9. List all special equipment, such as lifts, employee is trained and authorized to use.
- ☐ 10. Emergency Exits and Fire Extinguishers.

* Give a copy of these items to the employee.

I agree to abide by all company safety policies and the Code of Safe Practices. I also understand that failure to do so may result in disciplinary action and possible termination.

Signed _____ Date _____
Employee

Signed _____ Date _____
Supervisor

Supervisor

CODE OF SAFE PRACTICES RECEIPT

This is to certify that I have received a copy of the Code of Safe Practices. I have read these instructions, understand them, and will comply with them while working for the company.

I understand that failure to abide by these rules may result in disciplinary action and possible termination of my employment with the company.

I also understand that I am to report any injury to my Supervisor or Manager immediately and report all safety hazards.

I further understand that I have the following rights.

- I am not required to work in any area I feel is not safe.
- I am entitled to information on any hazardous material or chemical I am exposed to while working.
- I am entitled to see a copy of the Safety Manual and Injury and Illness Prevention Program.
- I will not be discriminated against for reporting safety concerns.

Print Name

Sign Name

Date

Copy: Employee
File

SAFETY COMMITTEE MEETING MINUTES

Date of Committee Meeting: _____ *Location:* _____

Minutes prepared by: _____ *Date:* _____

Review of Safety Inspection and Plan of Correction:

Previous Business: _____

New Business: _____

Review of Accidents: _____

Plan of Correction: _____

Employee Suggestions: _____

Recommended Safety Training: _____

Additional Comments: _____

Safety Committee Meeting Attendance:

- | | |
|----------|----------|
| 1. _____ | 2. _____ |
| 3. _____ | 4. _____ |
| 5. _____ | 6. _____ |

Sierra Trim, Inc.

IIPP/SAFETY MANUAL

- 7. _____
- 9. _____
- 11. _____
- 13. _____
- 15. _____
- 17. _____
- 19. _____

- 8. _____
- 10. _____
- 12. _____
- 14. _____
- 16. _____
- 18. _____
- 20. _____

SAFETY MEETING MINUTES

Company: _____ Department: _____

Presenter: _____ Date: _____

Safety Topic Discussed:

Additional items addressed other than topic:

Suggestions and Comments:

Safety Meeting Attendance:

- | | |
|-----------|-----------|
| 1. _____ | 2. _____ |
| 3. _____ | 4. _____ |
| 5. _____ | 6. _____ |
| 7. _____ | 8. _____ |
| 9. _____ | 10. _____ |
| 11. _____ | 12. _____ |
| 13. _____ | 14. _____ |
| 15. _____ | 16. _____ |
| 17. _____ | 18. _____ |

FACILITY INSPECTION CHECKLIST

Department/Division: _____

Date Of Inspection: _____

Location: _____

Inspector: _____

Criteria	Check One		Comments
	Yes	No	
• Are work areas properly illuminated?	☐	☐	
• Is the ventilation system appropriated for the work performed?	☐	☐	
• Are restrooms and washrooms kept clean and sanitary?	☐	☐	
• Is potable water provided for drinking and washing?	☐	☐	
• Are outlets for water not suitable for drinking clearly identified?	☐	☐	
• Where heat stress is a problem, do all fixed work areas have air conditioning?	☐	☐	
• Is the work area clean and orderly?	☐	☐	
• Are floors kept clean and dry or have you taken appropriate measures to make floors slip resistant?	☐	☐	
• Are floors free from protruding nails, splinters, holes, etc.?	☐	☐	
• Are permanent aisles and passageways clearly marked?	☐	☐	
• Are aisles and passageways kept clear?	☐	☐	
• Are pits and floor openings covered or guarded?	☐	☐	
• Is combustible trash removed from the worksite daily?	☐	☐	
• Are spilled materials or liquids cleaned up immediately?	☐	☐	
• Is there safe clearance in aisles where motorized or mechanical handling equipment travel?	☐	☐	
FLOOR AND WALL OPENINGS, STAIRS AND STAIRWAYS			
• Are floor openings guarded by covers or guardrails on all sides?	☐	☐	
• Do skylights have screens or fixed railings that would prevent someone on the roof from falling through?	☐	☐	
• Are open pits and trap doors guarded?	☐	☐	
• Are grates or similar type covers over floor openings such as floor drains, designed so that foot traffic or rolling equipment are not affected by grate spacing?	☐	☐	
• Are open-sided floors, platforms and runways having a drop of more than 4 feet guarded by a standard railing or toe board?	☐	☐	
• Are standard stair rails or handrails on all stairways having four or more risers?	☐	☐	
• Are all stairways at least 22 inches wide?	☐	☐	

- Do stairs have at least a 6-½ foot overhead clearance? - Are step risers on stairs uniform from top to bottom? - Are steps on stairs and stairways designed or provided with a slip-resistant surface? - Are stairway handrails located between 30 and 34 inches above the leading edge of stair treads?	☐ 	☐ 	
---	--	--	--

GENERAL WORK ENVIRONMENT

Criteria	Check One		Comments
	Yes	No	
Are stairway handrails capable of withstanding a load of 200 pounds, applied in any direction?	☐	☐	
ELEVATED SURFACES			
- Is the vertical distance between stairway landings limited to 12 feet or less? - Are stairways adequately illuminated? - Are signs posted showing the elevated surface load capacity? - Do elevated work areas have a permanent means of access and egress? - Are materials on elevated surfaces piled, stacked or racked in a manner to prevent tipping, falling, collapsing, rolling or spreading?	☐ 	☐ 	
EXITS AND EXIT DOORS			
- Are all exits marked with an exit sign and illuminated by a reliable light source? - Are exit routes clearly marked? - Are doors, passageways or stairways that are neither exits nor access to exits, appropriately marked "NOT AN EXIT" or "STOREROOM" etc.? - Are all exits kept free of obstructions? - Are there sufficient exits to permit prompt escape in case of emergency? - Do exit doors open in the direction of exit travel? - Are doors that swing in both directions provided with viewing panels in each door? - Are exits and exit routes equipped with emergency lighting?	☐ 	☐ 	
ADDITIONAL REMARKS:			

--	--	--	--

Additional information regarding this safety program manual can be obtained through the safety program administrator or safety committee.

